

1 Characteristics

Table 1. Absolute maximum ratings (limiting values)

Symbol	Parameters			Value	Unit
$I_{T(RMS)}$	On-state RMS current (180° conduction angle)		$T_L = 55^\circ\text{C}$	0.8	A
$I_{T(AV)}$	Average on-state current (180° conduction angle)			0.5	A
I_{TSM}	Non repetitive surge peak on-state current, T_j initial = 25 °C	$t_p = 8.3 \text{ ms}$	$T_j = 25^\circ\text{C}$	8	A
		$t_p = 10 \text{ ms}$		7	
I^2t	I^2t value for fusing	$t_p = 10 \text{ ms}$	$T_j = 25^\circ\text{C}$	0.24	A^2s
dI/dt	Critical rate of rise of on-state current $I_G = 2 \times I_{GT}, t_r \leq 100 \text{ ns}$	$F = 60 \text{ Hz}$	$T_j = 25^\circ\text{C}$	50	$\text{A}/\mu\text{s}$
V_{DRM} / V_{RRM}	Repetitive peak off-state voltage		$T_j = 125^\circ\text{C}$	400	V
I_{GM}	Peak gate current	$t_p = 20 \mu\text{s}$	$T_j = 125^\circ\text{C}$	1	A
$P_{G(AV)}$	Average gate power dissipation		$T_j = 125^\circ\text{C}$	0.1	W
T_{stg}	Storage junction temperature range			-40 to +150	°C
T_j	Operating junction temperature range			-40 to +125	°C

Table 2. Electrical characteristics ($T_j = 25^\circ\text{C}$, unless otherwise specified)

Symbol	Parameters	Value	Unit
I_{GT}	$V_D = 12 \text{ V}, R_L = 33 \Omega$	Max.	200
V_{GT}		Max.	0.8
V_{GD}	$V_D = V_{DRM}, R_L = 3.3 \text{ k}\Omega, R_{GK} = 1 \text{ k}\Omega, T_j = 125^\circ\text{C}$	Min.	0.1
V_{RG}	$I_{RG} = 10 \mu\text{A}$	Min.	8
I_H	$I_T = 50 \text{ mA}, R_{GK} = 1 \text{ k}\Omega$	Max.	5
I_L	$I_G = 1.2 I_{GT}, R_{GK} = 1 \text{ k}\Omega$	Max.	6
dV/dt	$V_D = 67 \% V_{DRM}, R_{GK} = 1 \text{ k}\Omega, T_j = 125^\circ\text{C}$	Min.	75
		V/ μs	

Table 3. Static electrical characteristics

Symbol	Test conditions	T_j	Value	Unit
V_T	$I_{TM} = 1.6 \text{ A}, t_p = 380 \mu\text{s}$	25 °C	Max.	1.95
V_{TO}	Threshold on-state voltage	125 °C	Max.	0.95
R_d	Dynamic resistance	125 °C	Max.	600
I_{DRM}	$V_D = V_{DRM}$	25 °C	Max.	1
I_{RRM}		125 °C		0.1
			mA	

Table 4. Thermal resistance

Symbol	Parameters	Max. value	Unit
$R_{th(j-l)}$	Junction to lead (DC)	80	
$R_{th(j-a)}$	Junction to ambient (DC)	150	°C/W

1.1 Characteristics (curves)

Figure 1. Maximum power dissipation versus on-state RMS current (full cycle)




Figure 2. Average and DC on-state current versus lead temperature




Figure 3. Average and DC on-state current versus ambient temperature




Figure 4. Relative variation of thermal impedance versus pulse duration




Figure 5. Relative variation of holding current versus gate-cathode resistance




Figure 6. Relative variation of gate voltage and gate, holding and latching current versus junction temperature




Figure 7. Relative variation of static dV/dt immunity versus gate-cathode resistance




Figure 8. Relative variation of dV/dt immunity versus gate-cathode capacitance




Figure 9. Surge peak on-state current versus number of cycles




Figure 10. Non-repetitive surge peak on-state current for sinusoidal pulse ($t_p < 10$ ms)





Figure 11. On-state characteristics (maximum values)



2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

2.1 TO-92 package information

- Lead free plating + halogen-free molding resin
- Epoxy meets UL94, VO

Figure 12. TO-92 package outline




Table 5. TO-92 package mechanical data

Ref.	Dimensions					
	Millimeters			Inches ⁽¹⁾		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A		1.35			0.0531	
B			4.70			0.1850
C		2.54			0.1000	
D	4.40			0.1732		
E	12.70			0.5000		
F			3.70			0.1457
a			0.50			0.0197
b		1.27			0.0500	
c			0.48			0.0189

1. Inches dimensions given for information

3 Ordering information

Figure 13. Ordering information scheme




Table 6. Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
P0102DA 1AA3	P0102 DA	TO-92	0.22 g	2500	Bag
P0102DA 2AL3				2000	AMMOPACK not in dry bag
P0102DA 5AL3				2000	Tape and reel 13"

Revision history

Table 7. Document revision history

Date	Revision	Changes
14-Oct-2019	1	Initial release.
18-May-2020	2	Updated Section Cover image.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[STMicroelectronics](#):

[P0102DA 5AL3](#) [P0102DA 1AA3](#) [P0102DA 2AL3](#)