

**ELECTRICAL CHARACTERISTICS** ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)

| DEVICE TYPE | BREAKDOWN VOLTAGE V_{BR} AT I_T ⁽¹⁾ (V) | | TEST CURRENT I_T (mA) | STAND-OFF VOLTAGE V_{WM} (V) | MAXIMUM REVERSE LEAKAGE AT V_{WM} ⁽³⁾ I_D (μ A) | MAXIMUM PEAK PULSE CURRENT I_{PPM} ⁽²⁾ (A) | MAXIMUM CLAMPING VOLTAGE AT I_{PPM} V_C (V) | MAXIMUM TEMPERATURE COEFFICIENT AT V_{BR} ($\%/^\circ\text{C}$) |
|-------------|--|------|-------------------------|--------------------------------|---|---|---|---|
| | MIN. | MAX. | | | | | | |
| (+)P6KE6.8A | 6.45 | 7.14 | 10 | 5.80 | 1000 | 57.1 | 10.5 | 0.057 |
| (+)P6KE7.5A | 7.13 | 7.88 | 10 | 6.40 | 500 | 53.1 | 11.3 | 0.061 |
| (+)P6KE8.2A | 7.79 | 8.61 | 10 | 7.02 | 200 | 49.6 | 12.1 | 0.065 |
| (+)P6KE9.1A | 8.65 | 9.55 | 1.0 | 7.78 | 50 | 44.8 | 13.4 | 0.068 |
| (+)P6KE10A | 9.50 | 10.5 | 1.0 | 8.55 | 10 | 41.4 | 14.5 | 0.073 |
| (+)P6KE11A | 10.5 | 11.6 | 1.0 | 9.40 | 5.0 | 38.5 | 15.6 | 0.075 |
| (+)P6KE12A | 11.4 | 12.6 | 1.0 | 10.2 | 5.0 | 35.9 | 16.7 | 0.078 |
| (+)P6KE13A | 12.4 | 13.7 | 1.0 | 11.1 | 5.0 | 33.0 | 18.2 | 0.081 |
| (+)P6KE15A | 14.3 | 15.8 | 1.0 | 12.8 | 1.0 | 28.3 | 21.2 | 0.084 |
| (+)P6KE16A | 15.2 | 16.8 | 1.0 | 13.6 | 1.0 | 26.7 | 22.5 | 0.086 |
| (+)P6KE18A | 17.1 | 18.9 | 1.0 | 15.3 | 1.0 | 23.8 | 25.2 | 0.088 |
| (+)P6KE20A | 19.0 | 21.0 | 1.0 | 17.1 | 1.0 | 21.7 | 27.7 | 0.090 |
| (+)P6KE22A | 20.9 | 23.1 | 1.0 | 18.8 | 1.0 | 19.6 | 30.6 | 0.092 |
| (+)P6KE24A | 22.8 | 25.2 | 1.0 | 20.5 | 1.0 | 18.1 | 33.2 | 0.094 |
| (+)P6KE27A | 25.7 | 28.4 | 1.0 | 23.1 | 1.0 | 16.0 | 37.5 | 0.096 |
| (+)P6KE30A | 28.5 | 31.5 | 1.0 | 25.6 | 1.0 | 14.5 | 41.4 | 0.097 |
| (+)P6KE33A | 31.4 | 34.7 | 1.0 | 28.2 | 1.0 | 13.1 | 45.7 | 0.098 |
| (+)P6KE36A | 34.2 | 37.8 | 1.0 | 30.8 | 1.0 | 12.0 | 49.9 | 0.099 |
| (+)P6KE39A | 37.1 | 41.0 | 1.0 | 33.3 | 1.0 | 11.1 | 53.9 | 0.100 |
| (+)P6KE43A | 40.9 | 45.2 | 1.0 | 36.8 | 1.0 | 10.1 | 59.3 | 0.101 |
| (+)P6KE47A | 44.7 | 49.4 | 1.0 | 40.2 | 1.0 | 9.3 | 64.8 | 0.101 |
| (+)P6KE51A | 48.5 | 53.6 | 1.0 | 43.6 | 1.0 | 8.6 | 70.1 | 0.102 |
| (+)P6KE56A | 53.2 | 58.8 | 1.0 | 47.8 | 1.0 | 7.8 | 77.0 | 0.103 |
| (+)P6KE62A | 58.9 | 65.1 | 1.0 | 53.0 | 1.0 | 7.1 | 85.0 | 0.104 |
| (+)P6KE68A | 64.6 | 71.4 | 1.0 | 58.1 | 1.0 | 6.5 | 92.0 | 0.104 |
| (+)P6KE75A | 71.3 | 78.8 | 1.0 | 64.1 | 1.0 | 5.8 | 103 | 0.105 |
| (+)P6KE82A | 77.9 | 86.1 | 1.0 | 70.1 | 1.0 | 5.3 | 113 | 0.105 |
| (+)P6KE91A | 86.5 | 95.5 | 1.0 | 77.8 | 1.0 | 4.8 | 125 | 0.106 |
| (+)P6KE100A | 95.0 | 105 | 1.0 | 85.5 | 1.0 | 4.4 | 137 | 0.106 |
| (+)P6KE110A | 105 | 116 | 1.0 | 94.0 | 1.0 | 3.9 | 152 | 0.107 |
| (+)P6KE120A | 114 | 126 | 1.0 | 102 | 1.0 | 3.6 | 165 | 0.107 |
| (+)P6KE130A | 124 | 137 | 1.0 | 111 | 1.0 | 3.4 | 179 | 0.107 |
| (+)P6KE150A | 143 | 158 | 1.0 | 128 | 1.0 | 2.9 | 207 | 0.108 |
| (+)P6KE160A | 152 | 168 | 1.0 | 136 | 1.0 | 2.7 | 219 | 0.108 |
| (+)P6KE170A | 162 | 179 | 1.0 | 145 | 1.0 | 2.6 | 234 | 0.108 |
| (+)P6KE180A | 171 | 189 | 1.0 | 154 | 1.0 | 2.4 | 246 | 0.108 |
| (+)P6KE200A | 190 | 210 | 1.0 | 171 | 1.0 | 2.2 | 274 | 0.108 |
| (+)P6KE220A | 209 | 231 | 1.0 | 185 | 1.0 | 1.8 | 328 | 0.108 |
| (+)P6KE250A | 237 | 263 | 1.0 | 214 | 1.0 | 1.7 | 344 | 0.110 |
| (+)P6KE300A | 285 | 315 | 1.0 | 256 | 1.0 | 1.4 | 414 | 0.110 |
| (+)P6KE350A | 333 | 368 | 1.0 | 300 | 1.0 | 1.2 | 482 | 0.110 |
| (+)P6KE400A | 380 | 420 | 1.0 | 342 | 1.0 | 1.1 | 548 | 0.110 |
| (+)P6KE440A | 418 | 462 | 1.0 | 376 | 1.0 | 1.00 | 602 | 0.110 |
| P6KE480A | 456 | 504 | 1.0 | 408 | 1.0 | 0.91 | 658 | 0.110 |
| P6KE510A | 485 | 535 | 1.0 | 434 | 1.0 | 0.86 | 698 | 0.110 |
| P6KE540A | 513 | 567 | 1.0 | 459 | 1.0 | 0.81 | 740 | 0.110 |

Notes

- (1) Pulse test: $t_p \leq 50\text{ ms}$
(2) Surge current waveform per fig. 3 and derate per fig. 2
(3) For bi-directional types with V_{WM} of 10 V and less the I_D limit is doubled
(4) All terms and symbols are consistent with ANSI/IEEE CA62.35
(5) Underwriters laboratory recognition for the classification of protectors (QVGG2) under the UL standard for safety 497B and file number E136766 for both uni-directional and bi-directional devices



| THERMAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | |
|--|-----------------|-------|--------------------|
| PARAMETER | SYMBOL | VALUE | UNIT |
| Typical thermal resistance, junction to lead | $R_{\theta JL}$ | 20 | $^\circ\text{C/W}$ |
| Typical thermal resistance, junction to ambient | $R_{\theta JA}$ | 75 | |

| ORDERING INFORMATION (Example) | | | | |
|--------------------------------|-----------------|------------------------|---------------|----------------------------------|
| PREFERRED PIN | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| P6KE6.8A-E3/54 | 0.432 | 54 | 4000 | 13" diameter paper tape and reel |
| P6KE6.8AHE3/54 ⁽¹⁾ | 0.432 | 54 | 4000 | 13" diameter paper tape and reel |

Note

⁽¹⁾ AEC-Q101 qualified

RATINGS AND CHARACTERISTICS CURVES ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Fig. 1 - Peak Pulse Power Rating Curve




Fig. 3 - Pulse Waveform




Fig. 2 - Pulse Power or Current vs. Initial Junction Temperature




Fig. 4 - Typical Junction Capacitance Uni-Directional




Fig. 5 - Power Derating Curve




Fig. 7 - Typical Transient Thermal Impedance





Fig. 6 - Maximum Non-Repetitive Forward Surge Current



PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

DO-15 (DO-204AC)



Note

- Dimensions of mold length and diameter do not include mold flash and gate burr, mold flash shall not exceed 0.015 inch per side. These dimensions are measured at the outermost extreme of the plastic body

APPLICATION NOTES

- This P6KE TVS series is a low cost commercial product for use in applications where large voltage transients can permanently damage voltage-sensitive components.
- The P6KE series device types are designed in a small package size where power and space is a consideration. They are characterized by their high surge capability, extremely fast response time, and low impedance, (R_{on}). Because of the unpredictable nature of transients, and the variation of the impedance with respect to these transients, impedance, per se, is not specified as a parametric value. However, a minimum voltage at low current conditions (V_c) and a maximum clamping voltage (V_c) at a maximum peak pulse current is specified.
- In some instances, the thermal effect (see V_c Clamping Voltage) may be responsible for 50 % to 70 % of the observed voltage differential when subjected to high current pulses for several duty cycles, thus making a maximum impedance specification insignificant.
- In case of a severe current overload or abnormal transient beyond the maximum ratings, the Transient Voltage Suppressor will initially fail 'short' thus tripping the system's circuit breaker or fuse while protecting the entire circuit. Curves depicting clamping voltage vs. various current pulses are available from the factory. Extended power curves vs. pulse time are also available.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

[P6KE100A-E3/54](#) [P6KE100AHE3/54](#) [P6KE10A-E3/54](#) [P6KE10AHE3/54](#) [P6KE110A-E3/54](#) [P6KE110AHE3/54](#)
[P6KE11A-E3/54](#) [P6KE11AHE3/54](#) [P6KE120A-E3/54](#) [P6KE120AHE3/54](#) [P6KE12A-E3/54](#) [P6KE12AHE3/54](#)
[P6KE130A-E3/54](#) [P6KE130AHE3/54](#) [P6KE13A-E3/54](#) [P6KE13AHE3/54](#) [P6KE150A-E3/54](#) [P6KE150AHE3/54](#)
[P6KE15A-E3/54](#) [P6KE15AHE3/54](#) [P6KE160A-E3/54](#) [P6KE160AHE3/54](#) [P6KE16A-E3/54](#) [P6KE16AHE3/54](#)
[P6KE170A-E3/54](#) [P6KE170AHE3/54](#) [P6KE180A-E3/54](#) [P6KE180AHE3/54](#) [P6KE18A-E3/54](#) [P6KE18AHE3/54](#)
[P6KE200A-E3/54](#) [P6KE200AHE3/54](#) [P6KE20A-E3/54](#) [P6KE20AHE3/54](#) [P6KE220A-E3/54](#) [P6KE220AHE3/54](#)
[P6KE22A-E3/54](#) [P6KE22AHE3/54](#) [P6KE24A-E3/54](#) [P6KE24AHE3/54](#) [P6KE27A-E3/54](#) [P6KE27AHE3/54](#)
[P6KE300A-E3/54](#) [P6KE30A-E3/54](#) [P6KE30AHE3/54](#) [P6KE33A-E3/54](#) [P6KE33AHE3/54](#) [P6KE350A-E3/54](#)
[P6KE36A-E3/54](#) [P6KE36AHE3/54](#) [P6KE39A-E3/54](#) [P6KE39AHE3/54](#) [P6KE400A-E3/54](#) [P6KE43A-E3/54](#)
[P6KE43AHE3/54](#) [P6KE440A-E3/54](#) [P6KE47A-E3/54](#) [P6KE47AHE3/54](#) [P6KE480A-E3/54](#) [P6KE510A-E3/54](#)
[P6KE51A-E3/54](#) [P6KE51AHE3/54](#) [P6KE540A-E3/54](#) [P6KE56A-E3/54](#) [P6KE56AHE3/54](#) [P6KE6.8A-E3/54](#)
[P6KE6.8AHE3/54](#) [P6KE62A-E3/54](#) [P6KE62AHE3/54](#) [P6KE68A-E3/54](#) [P6KE68AHE3/54](#) [P6KE7.5A-E3/54](#)
[P6KE7.5AHE3/54](#) [P6KE75A-E3/54](#) [P6KE75AHE3/54](#) [P6KE8.2A-E3/54](#) [P6KE8.2AHE3/54](#) [P6KE82A-E3/54](#)
[P6KE82AHE3/54](#) [P6KE9.1A-E3/54](#) [P6KE9.1AHE3/54](#) [P6KE91A-E3/54](#) [P6KE91AHE3/54](#)