

## RATINGS AND CHARACTERISTICS CURVES (TA=25°C unless otherwise noted)

Device (Note 1)	Device Marking Code	Nominal Zener Voltage			Test Current	Zener Impedance			Leakage Current		Maximum DC Zener Current
		Vz@Iz			IzT	ZzT@IzT	Zzk@Izk		IR@VR		IzM
		V			mA	Ω	Ω	mA	μA	V	mA(DC)
		Min.	Nom. (Notes 2)	Max.							
1SMA5926	926A	10.45	11	11.55	34.1	5.5	550	0.25	0.5	8.4	136
1SMA5927	927A	11.40	12	12.60	31.2	6.5	550	0.25	0.5	9.1	125
1SMA5928	928A	12.35	13	13.65	28.8	7.0	550	0.25	0.5	9.9	115
1SMA5929	929A	14.25	15	15.75	25.0	9.0	600	0.25	0.5	11.4	100
1SMA5930	930A	15.20	16	16.80	23.4	10.0	600	0.25	0.5	12.2	94
1SMA5931	931A	17.10	18	18.90	20.8	12.0	650	0.25	0.5	13.7	83
1SMA5932	932A	19.00	20	21.00	18.7	14.0	650	0.25	0.5	15.2	75
1SMA5933	933A	20.90	22	23.10	17.0	17.5	650	0.25	0.5	16.7	68
1SMA5934	934A	22.80	24	25.20	15.6	19.0	700	0.25	0.5	18.2	63
1SMA5935	935A	25.65	27	28.35	13.9	23.0	700	0.25	0.5	20.6	56
1SMA5936	936A	28.50	30	31.50	12.5	26.0	750	0.25	0.5	22.8	50
1SMA5937	937A	31.35	33	34.65	11.4	33.0	800	0.25	0.5	25.1	45
1SMA5938	938A	34.20	36	37.80	10.4	38.0	850	0.25	0.5	27.4	42
1SMA5939	939A	37.05	39	40.95	9.6	45.0	900	0.25	0.5	29.7	38
1SMA5940	940A	40.85	43	45.15	8.7	53.0	950	0.25	0.5	32.7	35
1SMA5941	941A	44.65	47	49.35	8.0	67.0	1000	0.25	0.5	35.8	32
1SMA5942	942A	48.45	51	53.55	7.3	70.0	1100	0.25	0.5	38.8	29
1SMA5943	943A	53.20	56	58.80	6.7	86.0	1300	0.25	0.5	42.6	27
1SMA5944	944A	58.90	62	65.10	6.0	100.0	1500	0.25	0.5	47.1	24
1SMA5945	945A	64.60	68	71.40	5.5	120.0	1700	0.25	0.5	51.7	22
1SMA5946	946A	71.25	75	78.75	5.0	140.0	2000	0.25	0.5	56.0	20
1SMA5947	947A	77.90	82	86.10	4.6	160.0	2500	0.25	0.5	62.2	18
1SMA5948	948A	86.45	91	95.55	4.1	200.0	3000	0.25	0.5	69.2	16
1SMA5949	949A	95.00	100	105.00	3.7	250.0	3100	0.25	0.5	76.0	15
1SMA5950	950A	104.50	110	115.50	3.4	300.0	4000	0.25	0.5	83.6	13
1SMA5951	951A	114.00	120	126.00	3.1	360.0	4500	0.25	0.5	91.2	12
1SMA5952	952A	123.50	130	136.50	2.9	450.0	5000	0.25	0.5	98.8	11
1SMA5953	953A	142.50	150	157.50	2.5	600.0	6000	0.25	0.5	114.0	10
1SMA5954	954A	152.00	160	168.00	2.3	700.0	6500	0.25	0.5	121.6	9
1SMA5955	955A	171.00	180	189.00	2.1	900.0	7000	0.25	0.5	136.8	8
1SMA5956	956A	190.00	200	210.00	1.9	1200.0	8000	0.25	0.5	152.0	7

## Notes:

1. Tolerance and Voltage Regulation Designation. The type number listed indicates a tolerance of ±5%
2. Vz limits are to be guaranteed at thermal equilibrium

FIG. 1 STEADY STATE POWER DERATING




FIG. 2 Vz = 12 THRU 68 VOLTS




FIG.3 ZENER VOLTAGE 12 TO 68 VOLTS




FIG. 4 EFFECT OF ZENER VOLTAGE




FIG.5 CAPACITANCE CURVE




FIG. 6 TYPICAL PULSE RATING CURVE




FIG. 7 PULSE WAVEFORM






FIG. 8 PULSE WAVEFORM




PACKAGE OUTLINE DIMENSIONS



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	1.27	1.58	0.050	0.062
B	4.06	4.60	0.160	0.181
C	2.29	2.83	0.090	0.111
D	1.99	2.50	0.078	0.098
E	0.90	1.41	0.035	0.056
F	4.95	5.33	0.195	0.210
G	0.10	0.20	0.004	0.008
H	0.15	0.31	0.006	0.012

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	1.68	0.066
B	1.52	0.060
C	3.93	0.155
D	2.41	0.095
E	5.45	0.215

MARKING DIAGRAM



- P/N = Device Marking Code
- G = Green Compound
- YW = Date Code
- F = Factory Code

### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Taiwan Semiconductor:

[1SMA5955 R3](#) [1SMA5952 R2](#) [1SMA5950 R3](#) [1SMA5948 R3](#) [1SMA5947 R2](#) [1SMA5952 R3](#) [1SMA5949 R2](#)  
[1SMA5953 R3](#) [1SMA5953 R2](#) [1SMA5954 R3](#) [1SMA5947 R3](#) [1SMA5954 R2](#) [1SMA5951 R2](#) [1SMA5948 R2](#)  
[1SMA5955 R2](#) [1SMA5956 R3](#) [1SMA5956 R2](#) [1SMA5946 R3](#) [1SMA5946 R2](#) [1SMA5949 R3](#) [1SMA5950 R2](#)  
[1SMA5951 R3](#) [1SMA5939 R2](#) [1SMA5942 R2](#) [1SMA5926 R2](#) [1SMA5938 R2](#) [1SMA5929 R2](#) [1SMA5940 R2](#)  
[1SMA5936 R2](#) [1SMA5933 R2](#) [1SMA5944 R2](#) [1SMA5930 R2](#) [1SMA5931 R2](#) [1SMA5945 R2](#) [1SMA5932 R2](#)  
[1SMA5935 R2](#) [1SMA5937 R2](#) [1SMA5941 R2](#) [1SMA5927 R2](#) [1SMA5943 R2](#) [1SMA5928 R2](#) [1SMA5934 R2](#)  
[1SMA5943 R3](#) [1SMA5928 R3](#) [1SMA5939 R3](#) [1SMA5929 R3](#) [1SMA5941 R3](#) [1SMA5938 R3](#) [1SMA5940 R3](#)  
[1SMA5934 R3](#) [1SMA5942 R3](#) [1SMA5931 R3](#) [1SMA5937 R3](#) [1SMA5945 R3](#) [1SMA5932 R3](#) [1SMA5926 R3](#)  
[1SMA5936 R3](#) [1SMA5944 R3](#) [1SMA5930 R3](#) [1SMA5933 R3](#) [1SMA5935 R3](#) [1SMA5949 R3G](#) [1SMA5953 R3G](#)  
[1SMA5941 R3G](#) [1SMA5937HR3](#) [1SMA5944HR2](#) [1SMA5930HR2](#) [1SMA5956 R3G](#) [1SMA5938 R2G](#) [1SMA5935HR3](#)  
[1SMA5940 R3G](#) [1SMA5953HR3](#) [1SMA5938HR2](#) [1SMA5950HR3](#) [1SMA5937 R3G](#) [1SMA5936HR2](#) [1SMA5939HR3](#)  
[1SMA5954HR3](#) [1SMA5948 R2G](#) [1SMA5929HR2](#) [1SMA5945 R3G](#) [1SMA5954HR2](#) [1SMA5935HR2](#) [1SMA5951](#)  
[R2G](#) [1SMA5936 R2G](#) [1SMA5933HR2](#) [1SMA5930 R2G](#) [1SMA5929 R3G](#) [1SMA5947HR3](#) [1SMA5955HR3](#)  
[1SMA5946HR3](#) [1SMA5937HR2](#) [1SMA5952 R2G](#) [1SMA5942HR2](#) [1SMA5932 R3G](#) [1SMA5928 R2G](#) [1SMA5950 R2G](#)  
[1SMA5931 R2G](#) [1SMA5934 R3G](#) [1SMA5939 R2G](#)