


GLOBAL PART NUMBER INFORMATION																
Global Part Numbering Example: WSC2515R7000FEA (visit www.vishay.net Vishay Dale parts numbering manual for all options)																
W	S	C	2	5	1	5	R	7	0	0	0	F	E	A		
GLOBAL MODEL		SIZE		VALUE ⁽¹⁾		TOLERANCE		PACKAGING				SPECIAL				
WSC WSN		01/2 2515 0002 4527 6927		R = decimal K = thousand R7000 = 0.70 Ω 1K500 = 1.5 kΩ		D = ± 0.5 % F = ± 1.0 % G = ± 2.0 % H = ± 3.0 % J = ± 5.0 % K = ± 10 %		EA = lead (Pb)-free, tape / reel EK = lead (Pb)-free, bulk TA = tin / lead, tape / reel (R86) BA = tin / lead, bulk (B43)				(dash number) (up to 2 digits) from 1 to 99 as applicable				

Notes

(1) WSC / WSN marking (www.vishay.com/doc?30327)

- Packaging code: EB (lead (Pb)-free) and TB (tin / lead) are non-standard packaging codes designating 1000 piece reels. These non-standard packaging codes are identical to our standard EA (lead (Pb)-free) and TA (tin / lead), except that they have a package quantity of 1000 pieces

DIMENSIONS in inches (millimeters)




GLOBAL MODEL	DIMENSIONS					SOLDER PAD DIMENSIONS		
	L	H	T	W	W ₁	a	b	L
WSC01/2	0.200 ± 0.020 (5.08 ± 0.508)	0.096 ± 0.015 (2.44 ± 0.381)	0.040 ± 0.010 (1.02 ± 0.254)	0.125 ± 0.005 (3.18 ± 0.127)	0.050 ± 0.010 (1.27 ± 0.254)	0.085 (2.16)	0.070 (1.78)	0.080 (2.03)
WSC2515	0.250 ± 0.020 (6.35 ± 0.508)	0.110 ± 0.015 (2.79 ± 0.381)	0.045 ± 0.010 (1.14 ± 0.254)	0.150 ± 0.005 (3.81 ± 0.127)	0.098 ± 0.010 (2.49 ± 0.254)	0.090 (2.29)	0.115 (2.92)	0.120 (3.05)
WSC0002	0.455 ± 0.020 (11.56 ± 0.508)	0.167 ± 0.010 (4.24 ± 0.254)	0.100 ± 0.010 (2.54 ± 0.254)	0.275 ± 0.005 (6.98 ± 0.127)	0.215 ± 0.005 (5.46 ± 0.127)	0.155 (3.94)	0.230 (5.84)	0.205 (5.21)
WSC4527	0.455 ± 0.020 (11.56 ± 0.508)	0.167 ± 0.010 (4.24 ± 0.254)	0.100 ± 0.010 (2.54 ± 0.254)	0.275 ± 0.005 (6.98 ± 0.127)	0.215 ± 0.005 (5.46 ± 0.127)	0.155 (3.94)	0.230 (5.84)	0.205 (5.21)
WSC6927	0.690 ± 0.032 (17.53 ± 0.813)	0.280 ± 0.015 (7.11 ± 0.381)	0.100 ± 0.010 (2.54 ± 0.254)	0.275 ± 0.005 (6.98 ± 0.127)	0.215 ± 0.015 (5.46 ± 0.381)	0.155 (3.94)	0.235 (5.97)	0.470 (11.94)


Notes


- 3D models available: www.vishay.com/doc?30328
- Surface mount solder profile recommendations: www.vishay.com/doc?31052
- Refer to WSC, WSN conversion guide for detailed construction drawings: www.vishay.com/doc?49616
- For WSC2515 0.5 % tolerance parts, W₁ terminal dimension will be 0.090" ± 0.015"

TEMPERATURE RISE



DERATING



PULSE CAPABILITY


www.vishay.com/resistors/SMD-wirewound-pulse-capability-calculator/

Note

- Pulse capability increases based on the amount of wire for the resistance value and construction. The WSC0002 has greater pulse capability than WSC4527 due to differences in internal construction. The non-inductive WSN has greater pulse capability for the same size WSC because the second layer of wire increases the wire mass available to withstand pulse energy without exceeding temperature limits. Follow pulse graphic link for more information regarding capability

PERFORMANCE		
TEST	CONDITIONS OF TEST	TEST LIMITS
Thermal shock	-55 °C to +150 °C, 1000 cycles, 15 min at each extreme	± 0.5 % + 0.05 Ω
Short time overload	5 x rated power for 5 s	± 0.2 % + 0.05 Ω
Low temperature storage	-65 °C for 24 h	± 0.2 % + 0.05 Ω
High temperature exposure	1000 h at +175 °C	± 0.5 % + 0.05 Ω
Bias humidity	+85 °C, 85 % RH, 10 % bias, 1000 h	± 0.2 % + 0.05 Ω
Mechanical shock	100 g's for 6 ms, 5 pulses	± 0.1 % + 0.05 Ω
Vibration	Frequency varied 10 Hz to 500 Hz in 1 min, 3 directions, 9 h	± 0.1 % + 0.05 Ω
Load life	1000 h at rated power, +70 °C, 1.5 h "ON", 0.5 h "OFF"	± 1.0 % + 0.05 Ω
Resistance to solder heat	+260 °C solder, 10 s to 12 s dwell, 25 mm/s emergence	± 0.5 % + 0.05 Ω

PACKAGING				
MODEL	REEL			
	TAPE WIDTH	DIAMETER	PIECES/REEL	CODE
WSC01/2	12 mm / embossed plastic	330 mm / 13"	2000	EA / TA
WSC2515	16 mm / embossed plastic	330 mm / 13"	2000	EA / TA
WSC0002, WSC4527	24 mm / embossed plastic	330 mm / 13"	1200	EA / TA
WSC6927	32 mm / embossed plastic	330 mm / 13"	725	EA / TA

Notes

- Embossed carrier tape per EIA-481
- Additional packaging details at www.vishay.com/doc?20051



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

[WSC01\22R000FTB](#) [WSC000130R10FBA](#) [WSC000262R00FTA](#) [WSC000225R50FTA](#) [WSC01\2R4000FTB](#)
[WSC01\21R210FTB](#) [WSC0001R2500FTB](#) [WSC00022R800FTA](#) [WSC000122R00FTB](#) [WSC000115R00FTB](#)
[WSC000120R00FTB](#) [WSC000147R00FBA](#) [WSC000113R70FBA](#) [WSC452720R00DBA](#) [WSC01\21R000FTB](#)
[WSC45275R000FEB](#) [WSC0001180R0FTB](#) [WSC00015R110FTB](#) [WSC01\22R700FTB](#) [WSC01\22R300FTB](#)
[WSC01\2R1500FTB](#) [WSC00021R210FTA](#) [WSC00011K000FTB](#) [WSC00022K340FTA](#) [WSC00011K500FTB](#)
[WSN00014R700FBA](#) [WSC01\2R5000FTB](#) [WSC01\2R1000FTB](#) [WSC01\2R2000FTB](#) [WSC01\2R3000FTB](#)
[WSC01\23R900FTB](#) [WSC01\2R3010FTB](#) [WSC01\21R000FEB](#) [WSC0002820R0JTA](#) [WSC0001R2490FEB](#)
[WSC25155R600FEB](#) [WSC2515220R0FEB](#) [WSC01\22R700FEB](#) [WSC25154R7FEB](#) [WSC01\2R1000FEB](#) [WSC-4527](#)
[.2 1%R86](#) [WSN-1 10 1%TR](#) [WSN-1 121 1%R86](#) [WSN-1 25 1%TR](#) [WSC0002R7000FTB](#) [WSC00012K000FTA](#)
[WSC0002R2200FTB](#) [WSC0001200R0FTA](#) [WSC00018R250FTA](#) [WSC00015R600FTA](#) [WSC0001R3300FEA](#) [WSC-2](#)
[2.74 1%R86](#) [WSC-2 6 1%R86](#) [WSN-2515 15 1%R86](#) [WSC25152R400FEA](#) [WSC0001124R0FBA](#)
[WSC0001133R0FBA](#) [WSC0001162R0FBA](#) [WSC00011K100FBA](#) [WSC00011K330FBA](#) [WSC00011K600JTA](#)
[WSC00011R020FBA](#) [WSC00011R960FBA](#) [WSC000120R50FTA](#) [WSC0001210R0FBA](#) [WSC0001243R0FBA](#)
[WSC000124R90FTB](#) [WSC0001261R0FBA](#) [WSC0001270R0JTA](#) [WSC000127R40FTA](#) [WSC00012K200JTA](#)
[WSC00012K670FBA](#) [WSC00012K700FBA](#) [WSC00012K770FBA](#) [WSC00012R610FBA](#) [WSC00012R700FBA](#)
[WSC0001374R0FBA](#) [WSC000139R20FBA](#) [WSC00013R160FBA](#) [WSC0001400R0FBA](#) [WSC000145R30FBA](#)
[WSC00014R640FBA](#) [WSC00014R990FBA](#) [WSC0001562R0FBA](#) [WSC000156R20FBA](#) [WSC00015R620FBA](#)
[WSC0001604R0FBA](#) [WSC000160R40FBA](#) [WSC0001619R0FBA](#) [WSC0001665R0FBA](#) [WSC000176R80FBA](#)
[WSC000180R60FBA](#) [WSC000191R00FBA](#) [WSC0001R1960FBA](#) [WSC0001R2370FBA](#) [WSC0001R2490FTB](#)
[WSC0001R2740FBA](#) [WSC0001R2870FBA](#) [WSC0001R3920FBA](#) [WSC0001R5110FBA](#)