

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)						
PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Static						
Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	BV_{DSS}	60	--	--	V
Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = 250\mu A$	$V_{GS(TH)}$	1	1.4	2.5	V
Gate-Source Leakage Current	$V_{GS} = \pm 20V, V_{DS} = 0V$	I_{GSS}	--	--	± 10	μA
Drain-Source Leakage Current	$V_{GS} = 0V, V_{DS} = 60V$	I_{DSS}	--	--	1	μA
	$V_{GS} = 0V, V_{DS} = 60V$ $T_J = 125^\circ\text{C}$		--	--	100	
Drain-Source On-State Resistance (Note 3)	$V_{GS} = 10V, I_D = 240mA$	$R_{DS(on)}$	--	1.5	2.5	Ω
	$V_{GS} = 4.5V, I_D = 220mA$		--	1.6	3	
Forward Transconductance (Note 3)	$V_{DS} = 5V, I_D = 240mA$	g_{fs}	--	0.5	--	S
Dynamic (Note 3)						
Total Gate Charge	$V_{GS} = 4.5V, V_{DS} = 30V,$ $I_D = 240mA$	Q_g	--	0.91	--	nC
Gate-Source Charge		Q_{gs}	--	0.33	--	
Gate-Drain Charge		Q_{gd}	--	0.32	--	
Input Capacitance	$V_{GS} = 0V, V_{DS} = 30V$ $f = 1.0MHz$	C_{iss}	--	30	--	pF
Output Capacitance		C_{oss}	--	15	--	
Reverse Transfer Capacitance		C_{rss}	--	6	--	
Switching (Note 3)						
Turn-On Delay Time	$V_{GS} = 10V, V_{DS} = 30V,$ $I_D = 240mA, R_G = 6\Omega$	$t_{d(on)}$	--	4	--	ns
Turn-On Rise Time		t_r	--	10	--	
Turn-Off Delay Time		$t_{d(off)}$	--	20	--	
Turn-Off Fall Time		t_f	--	50	--	
Source-Drain Diode						
Forward Voltage (Note 2)	$V_{GS} = 0V, I_S = 240mA$	V_{SD}	--	--	1.2	V
Reverse Recovery Time	$I_S = 240mA,$ $di/dt = 100A/\mu s$	t_{rr}	--	12	--	ns
Reverse Recovery Charge		Q_{rr}	--	3	--	nC

Notes:

1. Silicon limited current only.
2. Pulse test: Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
3. Switching time is essentially independent of operating temperature.


ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TSM2N7002KCU RFG	SOT-323	3,000pcs / 7" Reel


CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature




On-Resistance vs. Gate-Source Voltage




CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Capacitance vs. Drain-Source Voltage




BV_{DSS} vs. Junction Temperature




Maximum Safe Operating Area, Junction-to-Ambient



Source-Drain Diode Forward Current vs. Voltage






Normalized Thermal Transient Impedance, Junction-to-Ambient




PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)


SOT-323



SUGGESTED PAD LAYOUT (Unit: Millimeters)



MARKING DIAGRAM



- 72K** = Device code
 - F** = Site Code
 - Y** = Year Code
 - M** = Month code
- | | | | |
|---------------|---------------|---------------|---------------|
| O =Jan | P =Feb | Q =Mar | R =Apr |
| S =May | T =Jun | U =Jul | V =Aug |
| W =Sep | X =Oct | Y =Nov | Z =Dec |

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Taiwan Semiconductor:](#)

[TSM2N7002KCU](#)