## Rotation Sensing [High Performance]; 2-axis(X, Y plane) Field Operation;

S48E.pdf Oct.18,2013

Ta=25°C

Part Number	Type/Feature	Power Supply	Current Consumption	Sensitivity <sup>*1</sup>	PKG Type	Operating Temp. (°C)
MRSS29DR	Hi-voltage, Hi-speed	3.5 to 30.0V	1.5mA (Vcc12.0V)*2	3.2 mT< <sup>*3</sup>	3Pin MM	-40 to +85
MRUS72X	Low power, Hi-speed	2.4 to 3.6V	2.5mA (Vcc3.0V)*4	1.5 mT<	Mini 4Pin FLP	-40 to +85
MRUS74X	Ultra low power, Hi-speed	2.0 to 3.6V <sup>*5</sup>	2.5mA (VIH3.0V)*4	1.5 mT<	Mini 4Pin FLP	-40 to +105

\*1 The value indicates Hon sensitivity (Max).

\*2 Icc (Max) at Vcc12.0V

\*3 Condition: Magnetic field of 2mT is applied to Direction B (Y axis).

\*4 Peak current consumption. (Max) Avg. current consumption depends on Vcc/VIH input parameter settings.


\*5 Enable voltage (VIH)

## Package Types; Dimensions (in mm)

2.8±0.2








(in mm)

0.12+0.12

0 to 0.07 g

23±0





3Pin FLP (Type 3)











Mini 3Pin FLP (Type 5)



13±0.08

0.28±0.1


1.8±0.1



1.5±0.1

Mini 4Pin FLP (Type 7)

(\*) Pin Alignment for MRUS72, MRUS74 1.Gnd 2.Vdd 3.Enable 4.Out (in mm)



4Pin LLP (Type 6)

(in mm)

Package Type	Form of Packing	Pcs/Reel
3Pin MM 3Pin FLP Mini 3Pin FLP Mini 4Pin FLP	Tape & Reel	3,000
4Pin LLP	Tape & Reel	5,000



## Product Code System

#### AMR Sensors (Magnetic Switches)

(Part Number)

MRMS 2 01 A

#### Series Name

#### 2PKG Type

Туре	PKG Type
2	3Pin MM
3	3Pin FLP
5	Mini 3Pin FLP
6	4Pin LLP
7	Mini 4Pin LLP

#### OType

Туре	Туре	
01	Standard/Cost Reduction	
11	High Accuracy	
05	Standard/Cost Reduction (5V Type)	
15	High Accuracy (5V Type)	

### Caution for Use

## 1. Handling

• This product may be degraded by electrostatic discharge. It is necessary to take anti-static precautions when handling.

#### 2. Design

- Please evaluate this product for the magnet-variation of the magnet used along with this product, otherwise this product may result in the miss-operation or the nonoperation.
- Sensor miss-operation or non-operation may occur due to the influence of the magnetic noise from surrounding devices such as motor. Please make sure there is no influence of the magnetic noise in designing process.
- Please be careful about a magnetic body (Iron, Nickel, etc.) and a magnetic noise immunity that may affect the magnetism of a magnet.

#### Sensitivity Level (Type 01)

Туре	Sensitivity Level		
Α	Hon 2.5 mT / Hoff 0.5 mT		

#### Sensitivity Level (Type 11)

Туре	Sensitivity Level	
н	Hon 1.4 mT / Hoff 0.8 mT	
Μ	Hon 1.8 mT / Hoff 1.2 mT	
L	Hon 2.2 mT / Hoff 1.6 mT	

- Please do not supply inverse voltage or excess voltage to this product. If applied, this product may be damaged and electrically destroyed.
- Please design your product not to be affected by stress of the resin due to heat shrink. Also, please avoid corrosive gas that may erode the PCB wiring.
- It is effective to make the Vcc and GND line wide and short or to adopt multi-layer PCB for switching noise protection. In addition, please place a bypass capacitor near the sensor.

## EU RoHS Compliant

- $\cdot$  All the products in this catalog comply with EU RoHS.
- EU RoHS is "the European Directive 2002/95/EC on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment".
- For more details, please refer to our website 'Murata's Approach for EU RoHS' (http://www.murata.com/info/rohs.html).



## **∆Note:**

1. Export Control <For customers outside Japan>

No Murata products should be used or sold, through any channels, for use in the design, development, production, utilization, maintenance or operation of, or otherwise contribution to (1) any weapons (Weapons of Mass Destruction [nuclear, chemical or biological weapons or missiles] or conventional weapons) or (2) goods or systems specially designed or intended for military end-use or utilization by military end-users. <For customers in Japan>

For products which are controlled items subject to the "Foreign Exchange and Foreign Trade Law" of Japan, the export license specified by the law is required for export. 2. Please contact our sales representatives or product engineers before using the products in this catalog for the applications listed below, which require especially high reliability

for the prevention of defects which might directly damage a third party's life, body or property, or when one of our products is intended for use in applications other than those specified in this catalog. ② Aerospace equipment

- Aircraft equipment
- ③ Undersea equipment
- (5) Medical equipment
- 7 Traffic signal equipment
- (4) Power plant equipment

- ③ Data-processing equipment

- (6) Transportation equipment (vehicles, trains, ships, etc.)
- (8) Disaster prevention / crime prevention equipment
  - 1 Application of similar complexity and/or reliability requirements to the applications listed above

3. Product specifications in this catalog are as of September 2013. They are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. If there are any questions, please contact our sales representatives or product engineers.

- 4. Please read rating and (ACAUTION (for storage, operating, rating, soldering, mounting and handling) in this catalog to prevent smoking and/or burning, etc.
- 5. This catalog has only typical specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.
- 6. Please note that unless otherwise specified, we shall assume no responsibility whatsoever for any conflict or dispute that may occur in connection with the effect of our and/or a third party's intellectual property rights and other related rights in consideration of your use of our products and/or information described or contained in our catalogs. In this connection, no representation shall be made to the effect that any third parties are authorized to use the rights mentioned above under licenses without our consent.
- 7. No ozone depleting substances (ODS) under the Montreal Protocol are used in our manufacturing process.

# miRata Murata Manufacturing Co., Ltd.

http://www.murata.com/

Head Office 1-10-1, Higashi Kotari, Nagaokakyo-shi, Kyoto 617-8555, Japan Phone: 81-75-951-9111 International Division 3-29-12, Shibuya, Shibuya-ku, Tokyo 150-0002, Japan Phone: 81-3-5469-6123 Fax: 81-3-5469-6155 E-mail: intl@murata.co.jp



## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

MRMS211H MRMS215M MRMS211M