

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)										
PARAMETER	SYMBOL	MBRF 1035 CT	MBRF 1045 CT	MBRF 1050 CT	MBRF 1060 CT	MBRF 1090 CT	MBRF 10100 CT	MBRF 10150 CT	MBRF 10200 CT	UNIT
Critical rate of rise of off-state voltage	dv/dt	10,000								V/ μs
Junction temperature	T_J	-55 to +150								$^\circ\text{C}$
Storage temperature	T_{STG}	-55 to +150								$^\circ\text{C}$

Notes:

- $t_p = 2.0\mu\text{s}$, 1.0KHz

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	TYP	UNIT
Junction-to-case thermal resistance	$R_{\theta\text{JC}}$	3.5	$^\circ\text{C/W}$

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)						
PARAMETER		CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage per diode ⁽¹⁾	MBRF1035CT MBRF1045CT	$I_F = 5\text{A}, T_J = 25^\circ\text{C}$	V_F	-	0.70	V
	MBRF1050CT MBRF1060CT			-	0.80	V
	MBRF1090CT MBRF10100CT			-	0.85	V
	MBRF10150CT MBRF10200CT			-	0.88	V
	MBRF1035CT MBRF1045CT			$I_F = 10\text{A}, T_J = 25^\circ\text{C}$	-	0.80
	MBRF1050CT MBRF1060CT	-			0.90	V
	MBRF1090CT MBRF10100CT	-			0.95	V
	MBRF10150CT MBRF10200CT	-			0.98	V
	MBRF1035CT MBRF1045CT	$I_F = 5\text{A}, T_J = 125^\circ\text{C}$			-	0.57
	MBRF1050CT MBRF1060CT			-	0.65	V
	MBRF1090CT MBRF10100CT			-	0.75	V
	MBRF10150CT MBRF10200CT			-	0.78	V

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)						
PARAMETER		CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage per diode ⁽¹⁾	MBRF1035CT MBRF1045CT	$I_F = 10\text{A}, T_J = 125^\circ\text{C}$	V_F	-	0.67	V
	MBRF1050CT MBRF1060CT			-	0.75	V
	MBRF1090CT MBRF10100CT			-	0.85	V
	MBRF10150CT MBRF10200CT			-	0.88	V
Reverse current @ rated V_R per diode ⁽²⁾	MBRF1035CT MBRF1045CT MBRF1050CT MBRF1060CT MBRF1090CT MBRF10100CT MBRF10150CT MBRF10200CT	$T_J = 25^\circ\text{C}$	I_R	-	100	μA
	MBRF1035CT MBRF1045CT	$T_J = 125^\circ\text{C}$		-	15	mA
	MBRF1050CT MBRF1060CT			-	10	mA
	MBRF1090CT MBRF10100CT MBRF10150CT MBRF10200CT			-	5	mA

Notes:

1. Pulse test with $PW = 0.3\text{ms}$
2. Pulse test with $PW = 30\text{ms}$

ORDERING INFORMATION		
ORDERING CODE ⁽¹⁾⁽²⁾	PACKAGE	PACKING
MBRF10xCT	ITO-220AB	50 / Tube
MBRF10xCTH	ITO-220AB	50 / Tube

Notes:

1. "x" defines voltage from 35V(MBRF1035CT) to 200V(MBRF10200CT)
2. "H" means AEC-Q101 qualified

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics






Fig.5 Maximum Non-Repetitive Forward Surge Current




CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.6 Typical Transient Thermal Impedance



PACKAGE OUTLINE DIMENSIONS



DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	4.30	4.70	0.169	0.185
A2	2.30	2.96	0.091	0.117
b	0.50	0.90	0.020	0.035
b1	-	1.80	-	0.071
b2	0.95	1.45	0.037	0.057
c	0.46	0.76	0.018	0.030
c2	2.50	3.16	0.098	0.124
D	14.80	15.50	0.583	0.610
D1	2.40	3.20	0.094	0.126
D2	6.30	6.90	0.248	0.272
E	9.60	10.30	0.378	0.406
e	2.41	2.67	0.095	0.105
L	12.60	13.80	0.496	0.543
L4	-	4.10	-	0.161
P	3.00	3.40	0.118	0.134

MARKING DIAGRAM



- P/N = Marking Code
- G = Green Compound
- YWW = Date Code
- F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Taiwan Semiconductor:](#)

[MBRF10100CT](#) [MBRF10150CT](#) [MBRF10200CT](#) [MBRF1045CT](#) [MBRF1060CT](#) [MBRF10200CTH](#) [MBRF1060CTH](#)