

ABRIDGED DATA SHEET

MAX36051

DeepCover Security Manager
with 128 Bytes of Nonimprinting Memory

Ordering Information

PART	TEMP RANGE	PIN-PACKAGE
MAX36051+	-40°C to +85°C	16 CSBGA
MAX36051+TRL	-40°C to +85°C	16 CSBGA

+Denotes a lead(Pb)-free/RoHS compliant package.

TRL = Tape and reel.

Package Information

For the latest package outline information and land patterns (footprints), go to www.maximintegrated.com/packages. Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

PACKAGE TYPE	PACKAGE CODE	OUTLINE NO.	LAND PATTERN NO.
16 CSBGA	X16+1	21-0355	90-0334

ABRIDGED DATA SHEET

MAX36051

DeepCover Security Manager
with 128 Bytes of Nonimprinting Memory

Revision History

REVISION NUMBER	REVISION DATE	DESCRIPTION	PAGES CHANGED
0	4/10	Initial release	—
1	12/11	Corrected the comparator VIN reference in the <i>Recommended Operating Conditions</i> table; corrected the default Glitch Filter register (21h) value from 0Ah to AAh in the <i>Power-On Initialization</i> section	2, 13

For pricing, delivery, and ordering information, please contact Maxim Direct at 1-888-629-4642, or visit Maxim Integrated's website at www.maximintegrated.com.

Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time. The parametric values (min and max limits) shown in the Electrical Characteristics table are guaranteed. Other parametric values quoted in this data sheet are provided for guidance.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Maxim Integrated:](#)

[MAX36051+](#)