

## 2. Ordering Code

### 2.1 Green Package Options (Pb/Halide-free/RoHS Compliant)

Ordering Code <sup>(1)</sup>	Package	Operating Voltage	Max. Freq. (MHz)	Operation Range
AT25XE041B-SSHNHR-T	8S1	1.7V to 3.6V	85MHz	Extended (-40°C to +125°C)
AT25XE041B-SSHNHR-B				
AT25XE041B-MHNHR-T	8MA1			
AT25XE041B-MHNHR-Y				

1. The shipping carrier option code is not marked on the devices.

Package Type	
<b>8S1</b>	8-lead, 0.150" Wide, Plastic Gull Wing Small Outline Package (JEDEC SOIC)
<b>8MA1</b>	8-pad, 5 x 6 x 0.6mm, Thermally Enhanced Plastic Ultra Thin Dual Flat No-lead (UDFN)

## 3. Revision History

Revision Level – Release Date	History
A – June 2015	Initial release.

© 2015 Adesto Technologies. All rights reserved. / Rev.: DS-25XE041B-062A-6/2015 Addendum

Disclaimer: Adesto Technologies Corporation makes no warranty for the use of its products, other than those expressly contained in the Company's standard warranty which is detailed in Adesto's Terms and Conditions located on the Company's web site. The Company assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of Adesto are granted by the Company in connection with the sale of Adesto products, expressly or by implication. Adesto's products are not authorized for use as critical components in life support devices or systems.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Dialog Semiconductor:](#)

[AT25XE041B-MHNHR-T](#) [AT25XE041B-SSHNHR-T](#)