

SMD Schottky Barrier Rectifiers





RATING AND CHARACTERISTIC CURVES (MBR2030CT-G Thru. MBR20150CT-G)

FIG.1- Forward Current Derating Curve 25.0 Average Forward Current, (A) 20.0 15.0 10.0 Single Phase Half Wave 5.0 60Hz Resistive or Inductive Load 25 50 75 100 150 175 Case Temperature, (°C)












Marking Code

Part Number	Marking code	
MBR2030CT-G	MBR2030CT	
MBR2040CT-G	MBR2040CT	
MBR2050CT-G	MBR2050CT	
MBR2060CT-G	MBR2060CT	
MBR2080CT-G	MBR2080CT	
MBR20100CT-G	MBR20100CT	
MBR20150CT-G	MBR20150CT	



XXXX = Product type marking code ☐ = Compchip Logo

Standard Packaging

Case Type	TUBE PACK		
	TUBE (EA)	Box (EA)	CARTON (EA)
TO-220AB	50	2,000	8,000

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Comchip Technology:

 $\underline{\mathsf{MBR2060CT\text{-}G}} \ \underline{\mathsf{MBR2050CT\text{-}G}} \ \underline{\mathsf{MBR20100CT\text{-}G}} \ \underline{\mathsf{MBR2080CT\text{-}G}} \ \underline{\mathsf{MBR2030CT\text{-}G}} \ \underline{\mathsf{MBR20150CT\text{-}G}} \ \underline{\mathsf{MBR2040CT\text{-}G}}$