

Small Signal Product
ELECTRICAL CHARACTERISTICS (Ratings at $T_A=25^\circ\text{C}$ ambient temperature unless otherwise specified)

 V_F Forward Voltage = 1.2 V Maximum @ $I_F = 200$ mA for all types

Device Type	$V_Z @ I_{ZT}$ (V) Typ.	I_{ZT} (mA)	$Z_{ZT} @ O_{ZK}$ (Ω) Max.	I_{ZK} (mA)	$Z_{ZK} @ I_{ZK}$ (Ω) Max.	$I_R @ V_R$ (μA) Max.	V_R (V)
1N4728G	3.3	76	10	1	400	100	1
1N4729G	3.6	69	10	1	400	100	1
1N4730G	3.9	64	9	1	400	50	1
1N4731G	4.3	58	9	1	400	10	1
1N4732G	4.7	53	8	1	500	10	1
1N4733G	5.1	49	7	1	550	10	1
1N4734G	5.6	45	5	1	600	10	2
1N4735G	6.2	41	2	1	700	10	3
1N4736G	6.8	37	3.5	1	700	10	4
1N4737G	7.5	34	4	0.5	700	10	5
1N4738G	8.2	31	4.5	0.5	700	10	6
1N4739G	9.1	28	5	0.5	700	10	7
1N4740G	10	25	7	0.25	700	10	7.6
1N4741G	11	23	8	0.25	700	5	8.4
1N4742G	12	21	9	0.25	700	5	9.1
1N4743G	13	19	10	0.25	700	5	9.9
1N4744G	15	17	14	0.25	700	5	11.4
1N4745G	16	15.5	16	0.25	700	5	12.2
1N4746G	18	14	20	0.25	700	5	13.7
1N4747G	20	12.5	22	0.25	750	5	15.2
1N4748G	22	11.5	23	0.25	750	5	16.7
1N4749G	24	10.5	25	0.25	750	5	18.2
1N4750G	27	9.5	35	0.25	750	5	20.6
1N4751G	30	8.5	40	0.25	1000	5	22.8
1N4752G	33	7.5	45	0.25	1000	5	25.1
1N4753G	36	7	50	0.25	1000	5	27.4
1N4754G	39	6.5	60	0.25	1000	5	29.7
1N4755G	43	6	70	0.25	1500	5	32.7
1N4756G	47	5.5	80	0.25	1500	5	35.8
1N4757G	51	5	95	0.25	1500	5	38.8
1N4758G	56	4.5	110	0.25	2000	5	42.6

 Notes : 1. TOLERANCE AND TYPE NUMBER DESIGNATION (V_Z)

 The type numbers listed have a standard tolerance on the nominal zener voltage of $\pm 5\%$.

2. SPECIAL AVAILABLE INCLUDE

Nominal zener voltages shown and tighter voltage, for detailed information on price, availability and delivery, contact your nearest Taiwan Semiconductor representative.

 3. ZENER VOLTAGE (V_Z) MEASUREMENT

 The zener voltage (V_Z) is tested under pulse condition. The measured V_Z is guaranteed to be within specification with device junction in thermal equilibrium.

 4. ZENER IMPEDANCE (Z_Z) DERIVATION

 The zener impedance is derived from the 60-cycle ac voltage, which results when an ac current having an RMS value equal to 10% of the dc zener current (I_{ZT} or I_{ZK}) is superimposed to I_{ZT} or I_{ZK} .

Small Signal Product
ORDERING INFORMATION

PART NO.	PACKING CODE	GREEN COMPOUND CODE	PACKAGE	PACKING
1N47xxG (Note1,2)	R0	G	DO-41	5K / 14" Reel
	A0	G	DO-41	3K / BOX (Ammo)

Note 1: "xx" is Device Code from "28" through "58"


Note 2: Whole series with green compound.

EXAMPLE

PREFERRED PART NO.	PART NO.	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
1N4728G R0G	1N4728G	R0	G	Green compound

Small Signal Product

PACKAGE OUTLINE DIMENSIONS
DO-41



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	0.50	0.90	0.020	0.035
B	3.50	5.20	0.138	0.205
C	22.00	--	0.866	--
D	1.80	2.80	0.071	0.110

MARKING DIAGRAM



Small Signal Product**Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taiwan Semiconductor:

[1M110Z](#) [1M120Z](#) [1M130Z](#) [1M150Z](#) [1M160Z](#) [1M180Z](#) [1M200Z](#) [1N4741A](#) [1N4742A](#) [1N4743A](#) [1N4744A](#)
[1N4745A](#) [1N4746A](#) [1N4747A](#) [1N4748A](#) [1N4749A](#) [1N4750A](#) [1N4751A](#) [1N4752A](#) [1N4753A](#) [1N4754A](#) [1N4755A](#)
[1N4756A](#) [1N4757A](#) [1N4758A](#) [1N4759A](#) [1N4760A](#) [1N4761A](#) [1N4762A](#) [1N4763A](#) [1N4764A](#) [1N4740A](#) [1N4728G](#)
[1N4729G](#) [1N4730G](#) [1N4731G](#) [1N4732G](#) [1N4733G](#) [1N4734G](#) [1N4735G](#) [1N4736G](#) [1N4737G](#) [1N4738G](#) [1N4739G](#)
[1N4740G](#) [1N4741G](#) [1N4742G](#) [1N4743G](#) [1N4744G](#) [1N4745G](#) [1N4746G](#) [1N4747G](#) [1N4748G](#) [1N4749G](#)
[1N4750G](#) [1N4751G](#) [1N4752G](#) [1N4753G](#) [1N4754G](#) [1N4755G](#) [1N4756G](#) [1N4757G](#) [1N4758G](#) [1N4740A R0](#)
[1N4748A R0](#) [1N4762A R0](#) [1N4747A R0](#) [1N4741A R0](#) [1N4743A R0G](#) [1N4746AHR0](#) [1M150ZHR0G](#) [1N4740A R0G](#)
[1N4743AHR0](#) [1N4761A R0G](#) [1M130ZHR0G](#) [1N4758AHR0](#) [1N4754AHR0G](#) [1N4746AHR0G](#) [1N4764A R0G](#)
[1N4756A R0G](#) [1N4745AHR0G](#) [1N4745AHR0](#) [1N4752A R0G](#) [1N4758AHR0G](#) [1M120ZHR0](#) [1N4748AHR0](#)
[1N4761AHR0G](#) [1M160ZHR0](#) [1N4763A R0G](#) [1M120Z R0G](#) [1N4747A R0G](#) [1N4744AHR0](#) [1N4753A R0G](#)
[1M200ZHR0](#) [1M180ZHR0](#) [1N4742AHR0G](#) [1N4751AHR0G](#) [1N4760A R0G](#) [1N4746A R0G](#) [1N4759AHR0G](#)