


SMD Power Inductor CR54



Electrical Characteristics

Part Name	Stamp	Inductance (μ H) [within] ※ 1	D.C.R. (Ω) [Max.] (at 20°C)	Rated Current (A)※2
CR54NP-2R2MC	2R2	2.2 \pm 20 %	23.4m	3.84
CR54NP-2R7MC	2R7	2.7 \pm 20 %	26.0m	3.44
CR54NP-3R3MC	3R3	3.3 \pm 20 %	28.6m	3.20
CR54NP-3R9MC	3R9	3.9 \pm 20 %	35.1m	3.00
CR54NP-4R4MC	4R4	4.4 \pm 20 %	39.0m	2.80
CR54NP-5R0MC	5R0	5.0 \pm 20 %	44.2m	2.60
CR54NP-5R6MC	5R6	5.6 \pm 20 %	49.4m	2.48
CR54NP-6R4MC	6R4	6.4 \pm 20 %	52.0m	2.20
CR54NP-7R6MC	7R6	7.6 \pm 20 %	62.4m	2.08
CR54NP-8R5MC	8R5	8.5 \pm 20 %	67.6m	1.84
CR54NP-100MC	100	10 \pm 20 %	0.10	1.44
CR54NP-120MC	120	12 \pm 20 %	0.12	1.40
CR54NP-150MC	150	15 \pm 20 %	0.14	1.30
CR54NP-180MC	180	18 \pm 20 %	0.15	1.23
CR54NP-220MC	220	22 \pm 20 %	0.18	1.11
CR54NP-270MC	270	27 \pm 20 %	0.20	0.97
CR54NP-330LC	330	33 \pm 15 %	0.23	0.88
CR54NP-390LC	390	39 \pm 15 %	0.32	0.80
CR54NP-470LC	470	47 \pm 15 %	0.37	0.72
CR54NP-560KC	560	56 \pm 10 %	0.42	0.68
CR54NP-680KC	680	68 \pm 10 %	0.46	0.61
CR54NP-820KC	820	82 \pm 10 %	0.60	0.58
CR54NP-101KC	101	100 \pm 10 %	0.70	0.52
CR54NP-121KC	121	120 \pm 10 %	0.93	0.48
CR54NP-151KC	151	150 \pm 10 %	1.10	0.40
CR54NP-181KC	181	180 \pm 10 %	1.38	0.38
CR54NP-221KC	221	220 \pm 10 %	1.57	0.35

※1. Inductance measuring frequency: 2.2 μ H ~ 8.5 μ H ; at 7.96 MHz
 10 μ H ~ 82 μ H ; at 2.52 MHz
 100 μ H ~ 220 μ H ; at 1 kHz













※2. Rated current: The D.C. current at which the inductance decreases to 90% of its initial value or when $\Delta t=40^{\circ}\text{C}$, whichever is lower ($T_a=20^{\circ}\text{C}$).

SMD Power Inductor CR54



Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT






SMD Power Inductor CR54





Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT



Solder Reflow Condition



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong
Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Saitama(Japan)
Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Chicago
Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai
Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Seoul
Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Oberzell
Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen
Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore
Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

Neumarkt
Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei
Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose
Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Sumida:

[CR54NP-100MC](#) [CR54NP-150MC](#) [CR54NP-180MC](#) [CR54NP-220MC](#) [CR54NP-470LC](#) [CR54NP-680KC](#) [CR54NP-221KC](#) [CR54NP-330LC](#) [CR54NP-151KC](#) [CR54NP-4R4MC](#) [CR54NP-120MC](#) [CR54NP-7R6MC](#) [CR54NP-5R0MC](#) [CR54NP-8R2MC](#) [CR54NP-6R4MC](#) [CR54NP-560KC](#) [CR54NP-101KC](#) [CR54NP-7R4MC](#) [CR54NP-3R9MC](#) [CR54NP-121KC](#) [CR54NP-390LC](#) [CR54NP-2R2MC](#) [CR54NP-5R6MC](#) [CR54NP-8R5MC](#) [CR54NP-270MC](#) [CR54NP-2R7MC](#) [CR54NP-820KC](#) [CR54NP-181KC](#) [CR54NP-3R3MC](#)