





- A: SMD1210P005TS/TF B: SMD1210P010TS/TF C: SMD1210P020TS/TF D: SMD1210P035TS/TF E: SMD1210P050TS/TF
- F: SMD1210P075TS/TF G: SMD1210P110TS/TF
- H: SMD1210P150TS/TF

Thermal Derating Chart

Model	Ambient Operation Temperature - I _{hold} (A)								
	-40 °C	-20 °C	0°C	23 °C	40 °C	50 °C	60 °C	70 °C	85 °C
SMD1210P005TS/TF	0.08	0.07	0.06	0.05	0.04	0.04	0.03	0.03	0.02
SMD1210P010TS/TF	0.16	0.14	0.12	0.10	0.08	0.07	0.06	0.05	0.03
SMD1210P020TS/TF	0.29	0.26	0.22	0.20	0.16	0.14	0.13	0.11	0.08
SMD1210P035TS/TF	0.47	0.45	0.40	0.35	0.33	0.28	0.24	0.21	0.18
SMD1210P050TS/TF	0.76	0.67	0.58	0.50	0.43	0.40	0.36	0.32	0.28
SMD1210P075TS/TF	1.00	0.97	0.86	0.75	0.64	0.59	0.54	0.48	0.40
SMD1210P110TS/TF	1.69	1.48	1.29	1.10	0.88	0.76	0.65	0.57	0.43
SMD1210P150TS/TF	2.13	1.92	1.71	1.50	1.26	1.14	1.01	0.89	0.71

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse:

 SMD1210P150TFA
 SMD1210P010TFA
 SMD1206P150TFA
 SMD1210P035TFA
 SMD1206P035TFA

 SMD1210P020TFA
 SMD1210P005TFA
 SMD1206P075TFA
 SMD1210P075TFA
 SMD1206P100TFA

 SMD1206P025TFA
 SMD1206P100TSA
 SMD1210P010TSA
 SMD1206P075TSA
 SMD1206P035TSA

 SMD1206P012TSA
 SMD1210P020TSA
 SMD1210P050TSA
 SMD1206P020TSA
 SMD1210P150TSA

 SMD1210P005TSA
 SMD1206P012TFA
 SMD1210P050TFA
 SMD1206P050TFA
 SMD1206P020TFA

 SMD1206P035TF/15A
 SMD1210P110TFA
 SMD1206P016TFA
 SMD1210P035TSA
 SMD1210P110TSA

 SMD1210P075TSA
 SMD1206P150TSA
 SMD1206P050TSA