

3

2

1

ION
APR , 1997.
ERVED.

REVISIONS

変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

鉛フリー
LEAD FREE

		W2	W1	E	D	C	B	A	QTY/ REEL	POS	CONNECTOR P/N	TAPING P/N
OBSOLETE	WITH BOSS	36.7	33.5	0.4	22.2	32	28.4	14.2	1000	70	5-1747023-45	1747022-4
		49.5	45.5	0.38	24.7	40	40.4	20.2	1000	80	5-1747023-35	1747022-3
© OBSOLETE	WITHOUT BOSS	20.2	17.5	0.38	9.1	16	//	7.5	1000	20	1747026-9	1747025-9
OBSOLETE		29.5	25.5	0.38	16.6	24	//	11.5	1000	50	1747026-6	1747025-6
OBSOLETE	WITHOUT BOSS	37.5	33.5	0.38	19.1	32	28.4	14.2	1000	60	1747026-5	1747025-5
© OBSOLETE		37.5	33.5	0.38	21.6	32	28.4	14.2	1000	70	1747026-4	1747025-4
	WITHOUT BOSS	49.5	45.5	0.4	24.1	44	40.4	20.2	1000	80	1747023-3	1747025-3
		49.5	45.5	0.38	29.1	40	40.4	20.2	1000	100	1747026-1	1747025-1
	BOSS											

INSTRUCTION SHEET

取扱説明書

411-5808

WIRE RANGE

抱合電線断面積

-

INSULATION DIA

被覆外径

-

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

CHK

APVD

PRODUCT SPEC

製品規格

APPLICATION SPEC

取付適用規格

WEIGHT

CUSTOMER DRAWING



TE Connectivity

NAME
名称

ON TAPING (EMBOSS)
0.5mm PITCH FINE MATE CONN.
TAB ASSEMBLY (H-TYPE)

SIZE

CAGE CODE

DRAWING NO
番号

RESTRICTED TO

A3

00779

C-1747025

SCALE
尺度


4:1

SHEET

2 OF 2

REV

C1

DIMENSIONS:
単位: 耗
MMTOLERANCES UNLESS
OTHERWISE SPECIFIED:
一般公差

0 PLC	± 0.3
1 PLC	± 0.3
2 PLC	± 0.3
3 PLC	± 0.3
4 PLC	± 0.3
ANGLES	± 3°

MATERIAL
材料FINISH
仕上

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1747025-1](#)