


## Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Symbol	Min	Тур	Max	Units	Conditions
Collector-Base Breakdown Voltage	V <sub>(BR)CBO</sub>	-40			V	I <sub>C</sub> =-10μA, I <sub>E</sub> =0
Collector-Emitter Breakdown Voltage <sup>(2)</sup>	V <sub>(BR)CEO</sub>	-40			V	I <sub>C</sub> =-1mA, I <sub>B</sub> =0
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-5			V	I <sub>E</sub> =-10μA, I <sub>C</sub> =0
Collector-Base Cutoff Current	I <sub>CBO</sub>			-100	nA	V <sub>CB</sub> =-40V, I <sub>E</sub> =0
Collector Cutoff Current	I <sub>CEX</sub>			-50	nA	V <sub>CE</sub> =-30V, V <sub>BE</sub> =-3V
Emitter-Base Cutoff Current	I <sub>EBO</sub>			-100	nA	$V_{EB}$ =-5V, $I_C$ =0
	h <sub>FE(1)</sub>	100		300		V <sub>CE</sub> =-1V, I <sub>C</sub> =-10mA
DC Current Gain <sup>(2)</sup>	h <sub>FE(2)</sub>	60				$V_{CE}$ =-1V, $I_{C}$ =-50mA
	h <sub>FE(3)</sub>	30				V <sub>CE</sub> =-1V, I <sub>C</sub> =-100mA
Callector Emitter Saturation Valtage	V <sub>CE(sat)</sub>			-0.25	V	I <sub>C</sub> =-10mA, I <sub>B</sub> =-1mA
Collector-Emitter Saturation Voltage				-0.4	V	I <sub>C</sub> =-50mA, I <sub>B</sub> =-5mA
Page Emitter Saturation Valtage	V	-0.65		-0.85	V	I <sub>C</sub> =-10mA, I <sub>B</sub> =-1mA
Base-Emitter Saturation Voltage	$V_{BE(sat)}$			-0.95	V	I <sub>C</sub> =-50mA, I <sub>B</sub> =-5mA
Transition Frequency	f <sub>T</sub>	250			MHz	V <sub>CE</sub> =-20V, I <sub>C</sub> =-10mA, f=100MHz
Output Capacitance	C <sub>cbo</sub>			4.5	pF	V <sub>CB</sub> =-5V, I <sub>E</sub> =0, f=1MHz
Input Capacitance	C <sub>ibo</sub>			10	pF	$V_{BE}$ =-0.5V, $I_{C}$ =0, f=1MHz
Noise Figure	NF			4	dB	V <sub>CE</sub> =-5V, I <sub>C</sub> =100μA, R <sub>S</sub> =1K, f=1KHz
Delay Time	t <sub>d</sub>			35	ns	V <sub>CC</sub> =-3V, I <sub>C</sub> =-10mA
Rise Time	t <sub>r</sub>			35	ns	V <sub>BE</sub> =-0.5V, I <sub>B1</sub> =I <sub>B2</sub> =-1mA
Storage Time	t <sub>s</sub>			225	ns	V <sub>CC</sub> =-3V, I <sub>C</sub> =-10mA
Fall Time	t <sub>f</sub>			75	ns	I <sub>B1</sub> =I <sub>B2</sub> =-1mA

Note: 2. Pulse Width ≤ 300µs, Duty Cycle≤2.0%

# **Marking Information**



2A = Product Type Marking Code Y=Date Code Marking

## Date code Key (2 years a cycle)

Year	2011											
Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	J	0	L	С	K	В	Р	D	М	Е	G	F

Year	2012											
Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	W	N	Υ	Т	R	Н	Α	I	U	Х	Z	S



## **Curve Characteristics**








Fig. 2 - DC Current Gain Characteristics 300 non Emitter T<sub>A</sub>=100°C V<sub>CE</sub>= - 1V 250 200 DC Current Gain 150 100 50 0 -0.1 -10 -100 -200 Collector Current (mA)











### **Ordering Information**

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Rev.3-3-12012020 4/4 MCCSEMI.COM

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC): MMBT3906-TP