

Table 1. Electrical Specifications @ +25 °C¹, V_{DD} = 2.3-5.5V (Z_S = Z_L = 50Ω), unless otherwise specified

| Parameter | Path | Condition | Min | Typ | Max | Unit |
|-----------------------------|---------|--|-----|-----------------|-------------------|------|
| Operational frequency | | | 5 | | 6000 | MHz |
| Insertion loss ² | RFX-RFC | 5-100 MHz | | 0.23 | | dB |
| | | 100-1000 MHz | | 0.25 | 0.35 | dB |
| | | 1000-2000 MHz | | 0.30 | 0.40 | dB |
| | | 2000-3000 MHz | | 0.40 | 0.50 | dB |
| | | 3000-4000 MHz | | 0.50 | 0.70 | dB |
| | | 4000-5000 MHz | | 0.65 | 0.90 ² | dB |
| | | 5000-6000 MHz | | 0.90 | 1.25 ² | dB |
| Isolation | RFX-RFC | 5-100 MHz | | 68 | | dB |
| | | 100-1000 MHz | 42 | 44 | | dB |
| | | 1000-2000 MHz | 33 | 35 | | dB |
| | | 2000-3000 MHz | 27 | 29 | | dB |
| | | 3000-4000 MHz | 22 | 24 | | dB |
| | | 4000-5000 MHz | 18 | 20 | | dB |
| | | 5000-6000 MHz | 15 | 17 | | dB |
| Isolation | RFX-RFX | 5-100 MHz | | 61 | | dB |
| | | 100-1000 MHz | 40 | 41 | | dB |
| | | 1000-2000 MHz | 32 | 33 | | dB |
| | | 2000-3000 MHz | 26 | 28 | | dB |
| | | 3000-4000 MHz | 22 | 24 | | dB |
| | | 4000-5000 MHz | 18 | 20 | | dB |
| | | 5000-6000 MHz | 15 | 16 | | dB |
| Return loss ² | RFX-RFC | 5-100 MHz | | 33 | | dB |
| | | 100-1000 MHz | | 28 | | dB |
| | | 1000-2000 MHz | | 21 | | dB |
| | | 2000-3000 MHz | | 20 | | dB |
| | | 3000-4000 MHz | | 18 | | dB |
| | | 4000-5000 MHz | | 16 ² | | dB |
| | | 5000-6000 MHz | | 13 ² | | dB |
| 2nd harmonic | RFX-RFC | +18 dBm input power, 17-204 MHz | | -92 | | dBc |
| | | +32 dBm output power, 850 / 900 MHz | | -99 | | dBc |
| | | +32 dBm output power, 1800 / 1900 MHz | | -101 | | dBc |
| 3rd harmonic | RFX-RFC | +18 dBm input power, 17-204 MHz | | -125 | | dBc |
| | | +32 dBm output power, 850 / 900 MHz | | -93 | | dBc |
| | | +32 dBm output power, 1800 / 1900 MHz | | -87 | | dBc |
| IMD3 | RF-RFC | Bands I, II, V, VIII +17 dBm CW @ TX freq at RFC, -15 dBm CW @ 2Tx-Rx at RFC, 50Ω | | -115 | | dBm |

Table 1. Electrical Specifications @ +25 °C¹, V_{DD} = 2.3-5.5V (Z_S = Z_L = 50Ω), unless otherwise specified

| Parameter | Path | Condition | Min | Typ | Max | Unit |
|--|------------|---------------------------------------|-----|-----|-----|------|
| IIP2 | RFX | 5 MHz | | 96 | | dBm |
| | | 17 MHz | | 105 | | dBm |
| | | 100-6000 MHz | | 115 | | dBm |
| IIP3 | RFX | 5 MHz | | 75 | | dBm |
| | | 17 MHz | | 81 | | dBm |
| | | 100-6000 MHz | | 75 | | dBm |
| Input 0.1dB compression point ³ | RFX or RFC | 5-100 MHz | | 33 | | dBm |
| | | 100-6000 MHz | | 34 | | dBm |
| Switching time | | 50% CTRL to (10%-90%) or (90%-10%) RF | | 2 | 4 | μs |

Notes: 1. Typical performance over temperature and V_{DD} shown in *Figure 5* through *Figure 21*.

2. High frequency performance can be improved by external matching (see *Figure 22* through *Figure 27* and *Figure 30*).

3. The input P0.1dB compression point is a linearity figure of merit. Refer to *Table 5* for the operating RF input power.

Switching Frequency

The PE42427 has a maximum 25 kHz switching frequency. Switching frequency describes the time duration between switching events. Switching time is the time duration between the point the control signal reached 50% of the final value and the point the output signal reaches within 10% or 90% of its target value.

Spurious Performance

The PE42427 spur fundamental occurs around 13 MHz. Its typical performance is -163 dBm/Hz, with 200 kHz bandwidth. The performance is ideally suited for cable broadband applications.

Pin 4 should also be left unconnected for optimal spurious performance.

Thermal Data

Psi-JT (Ψ_{JT}), junction top-of-package, is a thermal metric to estimate junction temperature of a device on the customer application PCB (JEDEC JESD51-2).

$$\Psi_{JT} = (T_J - T_T)/P$$

where

Ψ_{JT} = junction-to-top of package characterization parameter, °C/W

T_J = die junction temperature, °C

T_T = package temperature (top surface, in the center), °C

P = power dissipated by device, Watts

Table 2. Thermal Data for PE42427

| Parameter | Typ | Unit |
|--|-----|------|
| Y _{JT} | 48 | °C/W |
| Q _{JA} junction-to-ambient thermal resistance | 145 | °C/W |

Figure 3. Pin Configuration (Top View)




Table 3. Pin Descriptions

| Pin No. | Pin Name | Description |
|---------|---------------------|--|
| 1 | GND | Ground |
| 2 | RF2 ¹ | RF port 2 |
| 3 | GND | Ground |
| 4 | GND/NC ² | Ground or no connect |
| 5 | RFC ¹ | RF common |
| 6 | GND | Ground |
| 7 | GND | Ground |
| 8 | RF1 ¹ | RF port 1 |
| 9 | DGND | Digital Ground |
| 10 | V1 | Switch control input, CMOS logic level |
| 11 | LS | Logic Select, CMOS logic level |
| 12 | V _{DD} | Supply |
| Pad | GND | Exposed pad: ground for proper operation |

Notes: 1. RF pins 2, 5 and 8 must be at 0 VDC. The RF pins do not required DC blocking capacitors for proper operation if the 0 VDC requirement is met.
2. Pin 4 can be grounded or left unconnected externally.

Table 4. Truth Table

| Path | V1 | LS |
|---------|----|----|
| RFC-RF2 | 1 | 1 |
| RFC-RF1 | 0 | 1 |
| RFC-RF1 | 1 | 0 |
| RFC-RF2 | 0 | 0 |

Table 5. Operating Ranges

| Parameter | Min | Typ | Max | Unit |
|--------------------------------------|-----|-----|--------|------|
| V _{DD} Supply voltage | 2.3 | 3.3 | 5.5 | V |
| I _{DD} Power supply current | | 180 | 300 | μA |
| RFX-RFC input power | | | Fig. 4 | dBm |
| Control voltage high | 1.2 | 1.5 | 3.3 | V |
| Control voltage low | 0 | 0 | 0.5 | V |
| Operating temperature range | -40 | +25 | +95 | °C |

Table 6. Absolute Maximum Ratings

| Parameter/Condition | Min | Max | Unit |
|--|-----|--------------|------------|
| RF input power, 50Ω ¹ 5-100 MHz 100-6000 MHz | | 33 34 | dBm dBm |
| ESD voltage HBM ² RF pins to GND All other pins | | 4000 1000 | V V |
| ESD voltage MM, all pins ³ | | 200 | V |
| T _{ST} Storage temperature | -65 | +150 | °C |

Notes: 1. V_{DD} within operating range specified in Table 5.
2. Human Body Model (MIL-STD 883 Method 3015.7).
3. Machine Model (JEDEC JESD22-A115-A).

Exceeding absolute maximum ratings may cause permanent damage. Operation should be restricted to the limits in the *Operating Ranges* table.

Electrostatic Discharge (ESD) Precautions

When handling this UltraCMOS device, observe the same precautions that you would use with other ESD-sensitive devices. Although this device contains circuitry to protect it from damage due to ESD, precautions should be taken to avoid exceeding the specified rating.


Latch-Up Avoidance

Unlike conventional CMOS devices, UltraCMOS devices are immune to latch-up.

Moisture Sensitivity Level

The Moisture Sensitivity Level rating for the PE42427 in the 12-lead 2 × 2 × 0.55 mm QFN package is MSL1.

Figure 4. Power De-rating Curve for 5-6000 MHz



Typical Performance Data @ +25 °C and $V_{DD} = 3.3V$, unless otherwise specified

Figure 5. Insertion Loss RFX*




Figure 6. Insertion Loss vs Temp (RF1-RFC)*




Figure 8. Insertion Loss vs V_{DD} (RF1-RFC)*




Figure 7. Insertion Loss vs Temp (RF2-RFC)*





Figure 9. Insertion Loss vs V_{DD} (RF2-RFC)*



Note: * High frequency performance can be improved by external matching (see Figure 22 through Figure 27 and Figure 30).

Typical Performance Data @ +25 °C and $V_{DD} = 3.3V$, unless otherwise specified (cont.)

Figure 10. RFX-RFX Isolation vs Temp




Figure 12. RFX-RFX Isolation vs V_{DD}




Figure 11. RFC-RFX Isolation vs Temp





Figure 13. RFC-RFX Isolation vs V_{DD}



Typical Performance Data @ +25 °C and $V_{DD} = 3.3V$, unless otherwise specified (cont.)

Figure 14. RFC Port Return Loss vs Temp (RF1 Active)*




Figure 16. RFC Port Return Loss vs V_{DD} (RF1 Active)*




Figure 15. RFC Port Return Loss vs Temp (RF2 Active)*





Figure 17. RFC Port Return Loss vs V_{DD} (RF2 Active)*



Note: * High frequency performance can be improved by external matching (see *Figure 22* through *Figure 27* and *Figure 30*).

Typical Performance Data @ +25 °C and $V_{DD} = 3.3V$, unless otherwise specified (cont.)

Figure 18. Active Port Return Loss vs Temp (RF1 Active)*




Figure 20. Active Port Return Loss vs V_{DD} (RF1 Active)*




Figure 19. Active Port Return Loss vs Temp (RF2 Active)*





Figure 21. Active Port Return Loss vs V_{DD} (RF2 Active)*



Note: * High frequency performance can be improved by external matching (see Figure 22 through Figure 27 and Figure 30).

Performance Comparison @ +25 °C and $V_{DD} = 3.3V$, with or without matching

Figure 22. Insertion Loss RF1*




Figure 25. Insertion Loss RF2*




Figure 23. Active Port Return Loss (RF1 Active)*




Figure 26. Active Port Return Loss (RF2 Active)*




Figure 24. RFC Port Return Loss (RF1 Active)*





Figure 27. RFC Port Return Loss (RF2 Active)*




Note: * High frequency performance can be improved by external matching (see Figure 22 through Figure 27 and Figure 30).

Evaluation Board

The SPDT switch evaluation board was designed to ease customer evaluation of pSemi’s PE42427. The RF common port is connected through a 50Ω transmission line via the top SMA connector, J2. RF1 and RF2 ports are connected through 50Ω transmission lines via SMA connectors J1 and J3, respectively. A through 50Ω transmission is available via SMA connectors J4 and J5. This transmission line can be used to estimate the loss of the PCB over the environmental conditions being evaluated. J8 provides DC and digital inputs to the device.

The board is constructed of a four metal layer material with a total thickness of 62 mils. The top and bottom RF layers are Rogers RO4350 material with a 10 mil RF core. The middle layers provide ground for the transmission lines. The transmission lines were designed using a coplanar waveguide with ground plane model using a trace width of 22 mils, trace gaps of 7 mils, and metal thickness of 2.1 mils.

Figure 28. Evaluation Board Layout



PRT-29005

Figure 29. Evaluation Board Schematic




Figure 30. Evaluation Board Schematic with Matching






Figure 31. Package Drawing
12-lead 2 × 2 × 0.55 mm QFN



12L_2x2x0-55_QFN_DOC-01882-3


Figure 32. Top Marking Specifications




DOC-66046

| Marking Spec Symbol | Package Marking | Definition |
|---------------------|-----------------|--|
| PP | EL | Part number marking for PE42427 |
| ZZ | 00-99 | Last two digits of lot code |
| YY | 00-99 | Last two digits of assembly year (Ex: 15 for 2015) |
| WW | 01-53 | Work week |

Figure 33. Tape and Reel Specifications
12-lead 2 × 2 × 0.55 mm QFN



| | Nominal | Tolerance |
|-----------|---------|-----------|
| Ao | 2.20 | ±0.1 |
| Bo | 2.20 | ±0.1 |
| Ko | 0.75 | ±0.1 |
| F | 3.50 | ±0.05 |
| P1 | 4.00 | ±0.1 |
| W | 8.00 | ±0.3 |



Device Orientation in Tape

- (I) Measured from centreline of sprocket hole to centreline of pocket.
- (II) Cumulative tolerance of 10 sprocket holes is ± 0.10 .
- (III) Measured from centreline of sprocket hole to centreline of pocket.
- (IV) Other material available.

This part shall not contain any banned substance as Sony standard SS-00259

Table 6. Ordering Information

| Order Code | Description | Package | Shipping Method |
|------------|--------------------------|---------------------------|-----------------|
| PE42427A-Z | PE42427 SPDT RF switch | Green 12-lead 2 × 2mm QFN | 3000 units T/R |
| EK42427-01 | PE42427 Evaluation board | Evaluation kit | 1/Box |

Sales Contact and Information

For sales and contact information please visit www.psemi.com.

Advance Information: The product is in a formative or design stage. The datasheet contains design target specifications for product development. Specifications and features may change in any manner without notice.
Preliminary Specification: The datasheet contains preliminary data. Additional data may be added at a later date. pSemi reserves the right to change specifications at any time without notice in order to supply the best possible product.
Product Specification: The datasheet contains final data. In the event pSemi decides to change the specifications, pSemi will notify customers of the intended changes by issuing a CNF (Customer Notification Form).
 The information in this document is believed to be reliable. However, pSemi assumes no liability for the use of this information. Use shall be entirely at the user's own risk. No patent rights or licenses to any circuits

described in this document are implied or granted to any third party. pSemi's products are not designed or intended for use in devices or systems intended for surgical implant, or in other applications intended to support or sustain life, or in any application in which the failure of the pSemi product could create a situation in which personal injury or death might occur. pSemi assumes no liability for damages, including consequential or incidental damages, arising out of the use of its products in such applications.
 The Peregrine Semiconductor name, Peregrine Semiconductor logo and UltraCMOS are registered trademarks and the pSemi name, pSemi logo, HaRP and DuNE are trademarks of pSemi Corporation in the U.S. and other countries.
 pSemi products are protected under one or more of the following U.S. Patents: <http://patents.psemi.com>.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

pSemi:

[EK42420-03](#) [PE42420D-Z](#) [PE42423MLBA-Z](#) [EK42423-02](#) [PE19601A-G](#) [EK19601-01](#) [4140-52](#) [EK42441-01](#)
[PE42441A-Z](#) [4141-00](#) [4141-52](#) [EK42462-01](#) [4140-00](#) [EK42412-01](#) [83336-00](#) [83336-21](#) [4246-52](#) [4246-00](#)
[EK42482-01](#) [PE4151MLAA-Z](#) [EK4151-01](#) [EK41901-01](#) [PE41901A-X](#) [EK426412-01](#) [4239-00](#) [4239-52](#)
[PE42521MLBA-Z](#) [EK426482-01](#) [EK42820-02](#) [PE42820MLBA-X](#) [EK43205-01](#) [PE43205MLAA-Z](#) [PE4314A-Z](#)
[EK4314-01](#) [EK42543-02](#) [PE42543A-X](#) [EK4312-11](#) [EK42553-01](#) [PE42553A-Z](#) [PE4312MLBA-Z](#) [EK42520-02](#)
[PE42520MLBA-Z](#) [PE42542A-X](#) [PE42850MLBA-X](#) [EK42850-03](#) [EK42522-02](#) [PE42522A-X](#) [PE42540LGBD-Z](#)
[EK42562-01](#) [EK64906-11](#) [PE64102MLAA-Z](#) [EK64102-11](#) [EK64908-11](#) [PE64908MLAA-Z](#) [PE64909MLAA-Z](#)
[EK64909-11](#) [EK44820-01](#) [PE64904MLBB-Z](#) [EK64904-12](#) [PE64907MLAA-Z](#) [EK64907-11](#) [EK43712-02](#) [PE43713A-Z](#)
[EK43713-02](#) [PE43705A-Z](#) [EK43705-11](#) [EK43711-02](#) [PE43711A-Z](#) [PE43712A-Z](#) [EK43704-11](#) [PE43704MLCA-Z](#)
[PE44820A-X](#) [EK64905-12](#) [PE64905MLBB-Z](#) [PE64101MLAA-Z](#) [EK64101-11](#) [EK42427-01](#) [PE42427A-Z](#) [EK42823-01](#)