

TOP ADJUSTMENT (Inch/mm)



SIDE ADJUSTMENT (Inch/mm)



STANDARD RESISTANCE VALUES, OHMS

10	100	1K	10K	50K	250K
20	200	2K	20K	100K	500K
50	500	5K	25K	200K	1Meg

Standard: Boxes

Capacity = 100 Units

Option: Tubes (83Y only)

All units oriented with #1 pin to same side.

Magazine: Width = 0.30"

Height = 0.35"

Length = 19.1"


Capacity = 50 Units

Option: Embossed Tape & Reel (83P only)


All units oriented with #1 pin to the right of the direction of feed.

Tape:	Width	=	16 mm	
	Sprocket	=	4 mm pitch	
	Capacity	=	1,000 Units	
Reel:	Diameter	=	14" (356 mm)	

ORDERING INFORMATION



CIRCUIT DIAGRAM



NOTES

Metric equivalents, based on 1 inch = 25.4mm are rounded to the same number of significant figures as in the original English units and are provided for general information only.

Tolerances unless otherwise specified: Linear = \pm .01 inches (.25mm) Angular = \pm 2 degrees





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TT Electronics:

 83PR500LF
 83PR1KLF
 83YR500LF
 83PR100KLF
 83PR2KLFTR
 83YR500LFTB
 83YR50KLF
 83YR1KLF

 83YR100KLFTB
 83YR50KLFTB
 83YR20KLFTB
 83YR20KLFTB
 83YR20KLFTB
 83YR20KLFTB
 83YR20KLFTB
 83YR50KLFTB
 83YR50KLFTB