

### Maximum Ratings † ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Part Number	Symbol	Value	Unit
Peak Repetitive Off-State Voltage (Note 1) ( $T_J = -40$ to $110^\circ\text{C}$ , Sine Wave, 50 to 60 Hz, Gate Open)	2N6400	$V_{\text{DRM}}$ , $V_{\text{RRM}}$	50	V
	2N6401		100	
	2N6402		200	
	2N6403		400	
	2N6404		600	
	2N6405		800	
On-State RMS Current ( $180^\circ$ Conduction Angles; $T_C = 100^\circ\text{C}$ )		$I_{\text{T (RMS)}}$	16	A
Average On-State RMS Current ( $180^\circ$ Conduction Angles; $T_C = 100^\circ\text{C}$ )		$I_{\text{T (AV)}}$	10	A
Peak Non–Repetitive Surge Current (1/2 Cycle, Sine Wave, 60 Hz, $T_J = 90^\circ\text{C}$ )		$I_{\text{TSM}}$	160	A
Circuit Fusing Considerations ( $t = 8.3$ ms)		$I^2t$	145	$\text{A}^2\text{s}$
Forward Peak Gate Power (Pulse Width $\leq 1.0$ $\mu\text{s}$ , $T_C = 100^\circ\text{C}$ )		$P_{\text{GM}}$	20	W
Forward Average Gate Power ( $t = 8.3$ ms, $T_C = 100^\circ\text{C}$ )		$P_{\text{G(AV)}}$	0.5	W
Forward Peak Gate Current (Pulse Width $\leq 1.0$ $\mu\text{s}$ , $T_C = 100^\circ\text{C}$ )		$I_{\text{GM}}$	2.0	A
Operating Junction Temperature Range		$T_J$	-40 to +125	$^\circ\text{C}$
Storage Temperature Range		$T_{\text{stg}}$	-40 to +125	$^\circ\text{C}$

† Indicates JEDEC Registered Data

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

- $V_{\text{DRM}}$  and  $V_{\text{RRM}}$  for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

### Maximum Ratings † ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta\text{JC}}$	1.5	$^\circ\text{C}/\text{W}$
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 10 seconds	$T_L$	260	$^\circ\text{C}$

† Indicates JEDEC Registered Data

### Electrical Characteristics - OFF ( $T_c = 25^\circ\text{C}$ unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
†Peak Repetitive Blocking Current ( $V_{AK} = V_{DRM} = V_{RRM}$ ; Gate Open)	$T_J = 25^\circ\text{C}$	$I_{DRM}$	-	-	1.0	$\mu\text{A}$
	$T_J = 125^\circ\text{C}$	$I_{RRM}$	-	-	2.0	mA

### Electrical Characteristics - ON

Characteristic		Symbol	Min	Typ	Max	Unit
†Peak Forward On-State Voltage ( $I_{TM} = 32\text{ A Peak}$ , Pulse Width $\leq 1\text{ ms}$ , Duty Cycle $\leq 2\%$ )		$V_{TM}$	-	-	1.7	V
†Gate Trigger Voltage (Continuous DC), All Quadrants (Continuous dc) ( $V_D = 12\text{ Vdc}$ , $R_L = 100\ \Omega$ )	$T_c = 25^\circ\text{C}$	$I_{GT}$	-	9.0	30	mA
	$T_c = -40^\circ\text{C}$		-	-	60	
†Gate Trigger Voltage (Continuous dc) ( $V_D = 12\text{ Vdc}$ , $R_L = 100\ \Omega$ )	$T_c = 25^\circ\text{C}$	$V_{GT}$	-	0.7	1.5	V
	$T_c = -40^\circ\text{C}$		-	-	2.5	
Gate Non-Trigger Voltage ( $V_D = 12\text{ Vdc}$ , $R_L = 100\ \Omega$ )	$T_c = +125^\circ\text{C}$	$V_{GD}$	0.2	-	-	V
†Holding Current ( $V_D = 12\text{ Vdc}$ , Initiating Current = 200 mA, Gate Open)	$T_c = 25^\circ\text{C}$	$I_H$	-	18	40	mA
	$T_c = -40^\circ\text{C}$		-	-	60	
Turn-On Time ( $I_{TM} = 12\text{ A}$ , $I_{GT} = 40\text{ mAdc}$ , $V_D = \text{Rated } V_{DRM}$ )		$t_{gt}$	-	1.0	-	$\mu\text{s}$
Turn-Off Time ( $I_{TM} = 16\text{ A}$ , $I_R = 16\text{ A}$ , $V_D = \text{Rated } V_{DRM}$ )	$T_c = 25^\circ\text{C}$	$t_q$	-	15	-	$\mu\text{s}$
	$T_J = +125^\circ\text{C}$		-	35	-	


†Indicates JEDEC Registered Data

### Dynamic Characteristics


Characteristic		Symbol	Min	Typ	Max	Unit
Critical Rate-of-Rise of Off-State Voltage ( $V_D = \text{Rated } V_{DRM}$ , Exponential Waveform)	$T_J = +125^\circ\text{C}$	$dv/dt(c)$	-	50	-	$\text{V}/\mu\text{s}$

### Voltage Current Characteristic of SCR


Symbol	Parameter
$V_{DRM}$	Peak Repetitive Forward Off State Voltage
$I_{DRM}$	Peak Forward Blocking Current
$V_{RRM}$	Peak Repetitive Reverse Off State Voltage
$I_{RRM}$	Peak Reverse Blocking Current
$V_{TM}$	Maximum On State Voltage
$I_H$	Holding Current




**Figure 1. Current Derating**




**Figure 2. Maximum On-State Power Dissipation**




**Figure 3. On-State Characteristics**



**Figure 4. Maximum Non-Repetitive Surge Current**




**Figure 5. Thermal Response**




### Typical Characteristics


**Figure 6. Typical Gate Trigger Current vs. Pulse Width**




**Figure 7. Typical Gate Trigger Current vs. Junction Temperature**




**Figure 8. Typical Gate Trigger Voltage vs. Junction Temperature**



**Figure 9. Typical Holding Current vs. Junction Temperature**




### Dimensions



Dim	Inches		Millimeters	
	Min	Max	Min	Max
A	0.570	0.620	14.48	15.75
B	0.380	0.405	9.66	10.28
C	0.160	0.190	4.07	4.82
D	0.025	0.035	0.64	0.88
F	0.142	0.147	3.61	3.73
G	0.095	0.105	2.42	2.66
H	0.110	0.155	2.80	3.93
J	0.014	0.022	0.36	0.55
K	0.500	0.562	12.70	14.27
L	0.045	0.060	1.15	1.52
N	0.190	0.210	4.83	5.33
Q	0.100	0.120	2.54	3.04
R	0.080	0.110	2.04	2.79
S	0.045	0.055	1.15	1.39
T	0.235	0.255	5.97	6.47
U	0.000	0.050	0.00	1.27
V	0.045	---	1.15	---
Z	---	0.080	---	2.04

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

### Part Marking System



TO-220AB  
CASE 221A  
STYLE 3

x= 0, 1, 2, 3, 4 or 5  
A= Assembly Location  
Y= Year  
WW = Work Week  
G= Pb-Free Package

### Pin Assignment

1	Cathode
2	Anode
3	Gate
4	Anode

### Ordering Information

Device	Package	Shipping
2N6400G	TO-220AB (Pb-Free)	500 Units / Box
2N6401G		
2N6402G		
2N6403G		
2N6403TG		50 Units / Rail
2N6404G		500 Units / Box
2N6405G		

**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Littelfuse:](#)

[2N6405G](#) [2N6400G](#) [2N6402G](#) [2N6401G](#) [2N6403G](#) [2N6404G](#) [2N6403TG](#)