

TECHNICAL INFORMATION

MATERIAL

- Insulator: High temperature thermal plastic (UL94V-0), color option
- Contacts: Copper alloy, gold flash or 15 microinches min. of gold or 30 microinches min. of gold (Contact area), tin or matte tin plating (solder area), nickel plating over all (underplate)
- Boardlock: Copper alloy, tin plating (solder area), nickel plating overall (underplate)

ELECTRICAL PERFORMANCE

- Voltage Rating: 30V AC (RMS)/DC
- Current Rating (0.7A/pin max.

MECHANICAL PERFORMANCE

- Insertion Force: 10.88Kgf max.
- Withdrawal Force: 14gf min. per contact pair
- Retention Force: Contact: 0.30Kgf min.
- Boardlock: 1.36Kgf min.
- Durability
- Vibration, Mechanical Shock
- Latch Overstress Force (3.5kg min. force held for 10s with no damage)
- Reseating – No damage
- Latch Actuation Force – The force to fully actuate the latch open shall be 4.5kgf max. per latch
- Module Rip Out Force – 9.1kgf min. retention force of the module in connector with no damage
- Retention of Connector to PCB – No lifting of connector from applicable PCB
- Total Insertion force to be 6.8kgf max.

SPECIFICATIONS

Amphenol:

- Product Specification: GS-12-1092
- Packaging Specification: GS-14-2267
- Application Specification: GS-20-0353

JEDEC:

- Module Outline: MO-309
- Socket Outlines:
 - PTH solder: SO-016
 - Surface-Mount: SO-017
 - Press-fit: SO-019

APPROVALS & CERTIFICATION

- UL E66906

ENVIRONMENTAL

- Solderability (Solder coverage – 95% min.)
- Resistance to Soldering Heat (Visual: no damage or discoloration of connector materials)
- Temperature life, Thermal shock
- Cycling temperature and humidity
- Temperature Rise: 30°C max.
- Mixed Flowing Gas, Thermal Disturbance, Salt Spray

PACKAGING

- Tray

TARGET MARKETS/APPLICATIONS



Routers
Switches
Wireless Infrastructure



Desktop PCs
Servers
Storage Systems
Supercomputers
Workstations



Embedded Systems

PART NUMBERS

Description	Features	Part Numbers
DDR4 Surface Mount (SMT) with forklocks, solder tabs or SMT hold downs, and dust cap	Standard	10145891* / DDR4-288-S*
	With cap	10136830*
	Tall housing	10135356*
DDR4 Plated Through Hole (PTH) with forklocks and Pin-in-Paste version	Standard	10145226* / DDR4-288-V*
	Pin-in-Paste	10136688*
	Ultra low profile	10129206*
	Single latch	10144512*
	Longer tail length	10144327*
DDR4 Press-fit (PF) with post	Standard	10124806*

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[DDR4288S0513TF](#) [DDR4288S0523TF](#) [DDR4288V0123T](#)

FCI / Amphenol:

[10124806-01006LF](#) [10124677-0001001LF](#) [DDR4288V0111T](#) [DDR4288S0211TF](#) [DDR4288S0221TF](#)
[DDR4288S0511TF](#) [DDR4288S0521TF](#) [DDR4288V0111TF](#) [DDR4288V0113TF](#) [DDR4288V0121TF](#)
[DDR4288V0123TF](#) [DDR4288V0211TF](#) [DDR4288V0213TF](#) [DDR4288V0221TF](#) [DDR4288V0223TF](#) [10124677-](#)
[0001303LF](#) [10124677-0301106LF](#) [10124677-0301006LF](#) [10124677-0311403LF](#) [10124677-0621403LF](#) [10124677-](#)
[0100E13LF](#) [10124677-0021D03LF](#) [10124677-1612301LF](#) [10124677-1611301LF](#) [10124677-0301K13LF](#) [10124677-](#)
[0201116LF](#) [10124677-1611001LF](#) [10124677-1612001LF](#) [10124677-0001K03LF](#) [10124677-0121F13LF](#) [10124677-](#)
[0131F14LF](#) [10124677-0120E13LF](#) [10124677-0611001LF](#) [10124677-0301103LF](#) [10124677-0501D01LF](#) [10124677-](#)
[1602001LF](#) [10124677-1601001LF](#) [10124677-0101E13LF](#) [10124677-0001403LF](#) [10124677-0000J03LF](#) [10124677-](#)
[0021D01LF](#) [10124677-0301C03LF](#) [10124677-0021101LF](#) [10124677-0501101LF](#) [10124677-0130E13LF](#) [10124677-](#)
[0311C03LF](#) [10124677-0131F13LF](#) [10124677-0301J13LF](#) [10124677-0101011LF](#) [10124677-0311B03LF](#) [10124677-](#)
[0501103LF](#) [10124677-0301011LF](#) [10124677-0501F03LF](#) [10124677-0301B03LF](#) [10124677-0301114LF](#) [10124677-](#)
[0101S03LF](#) [10124677-0100303LF](#) [10124677-0101303LF](#) [10124677-0201003LF](#) [10124677-0020103LF](#) [10124677-](#)
[0301013LF](#) [10124677-0001716LF](#) [10124677-0021103LF](#) [10124677-0000001LF](#) [10124632-0341K03LF](#) [10124632-](#)
[0341M03LF](#) [10124632-0341J03LF](#) [10124632-020100GLF](#) [10124632-020110GLF](#) [10124632-020000GLF](#) [10124677-](#)
[0301S03LF](#) [10124677-0000716LF](#) [10124806-01103LF](#) [10124806-01116LF](#) [10124806-01306LF](#) [10124806-01406LF](#)
[10124806-01111LF](#) [10124806-01001LF](#) [10124806-01403LF](#) [10124806-01101LF](#) [10124806-01303LF](#) [10124806-](#)
[01106LF](#) [10124806-01113LF](#) [10124806-01416LF](#) [10124806-00014LF](#) [10124806-01114LF](#) [10124677-1301003LF](#)
[10135356-0320J11LF](#) [10124677-0501S01LF](#) [10124632-2053016LF](#) [10124677-0501P01LF](#) [10124632-0201S03LF](#)
[10124632-0200R01LF](#) [10124632-0211R13LF](#) [10124632-0230R16LF](#) [10124632-0201V01LF](#) [10124632-2051016LF](#)
[10124632-0200R03LF](#) [10124632-2011003LF](#) [10124632-0251S01LF](#)