



SMD1210

A: SMD1210P005TS/TF B: SMD1210P010TS/TF C: SMD1210P020TS/TF D: SMD1210P035TS/TF E: SMD1210P050TS/TF F: SMD1210P075TS/TF G: SMD1210P110TS/TF H: SMD1210P150TS/TF

Thermal Derating Chart

Model	Ambient Operation Temperature - I _{hold} (A)								
	-40 °C	-20 °C	0 °C	23 °C	40 °C	50 °C	60 °C	70 °C	85 °C
SMD1210P005TS/TF	0.08	0.07	0.06	0.05	0.04	0.04	0.03	0.03	0.02
SMD1210P010TS/TF	0.16	0.14	0.12	0.10	0.08	0.07	0.06	0.05	0.03
SMD1210P020TS/TF	0.29	0.26	0.22	0.20	0.16	0.14	0.13	0.11	0.08
SMD1210P035TS/TF	0.47	0.45	0.40	0.35	0.33	0.28	0.24	0.21	0.18
SMD1210P050TS/TF	0.76	0.67	0.58	0.50	0.43	0.40	0.36	0.32	0.28
SMD1210P075TS/TF	1.00	0.97	0.86	0.75	0.64	0.59	0.54	0.48	0.40
SMD1210P110TS/TF	1.69	1.48	1.29	1.10	0.88	0.76	0.65	0.57	0.43
SMD1210P150TS/TF	2.13	1.92	1.71	1.50	1.26	1.14	1.01	0.89	0.71

040606

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse:

SMD1210P150TFASMD1210P010TFASMD1206P150TFASMD1210P035TFASMD1206P035TFASMD1210P020TFASMD1210P005TFASMD1206P075TFASMD1210P075TFASMD1206P100TFASMD1206P025TFASMD1206P100TSASMD1210P010TSASMD1206P075TSASMD1206P035TSASMD1206P012TSASMD1210P020TSASMD1210P050TSASMD1206P020TSASMD1210P150TSASMD1210P005TSASMD1206P012TFASMD1210P050TFASMD1206P020TFASMD1206P020TFASMD1206P035TF/15ASMD1210P110TFASMD1206P016TFASMD1210P035TSASMD1210P110TSASMD1210P075TSASMD1206P150TSASMD1206P050TSASMD1210P110TSA