

Electrical Characteristics2 – Standard Type

PART NO.	STAMP	INDUCTANCE (μ H) ※1	D.C.R. (m Ω) [MAX.] (at 20°C)	SATURATION CURRENT (A) ※2		TEMPERATURE RISE CURRENT (A) ※3 Δ T=40°C
				(at 20°C)	(at100°C)	
CDEP105NP-0R2NC-50	0R2NS	0.22 \pm 30%	1.7(1.4)	40.0	30.9	19.0
CDEP105NP-0R4MC-50	0R4MS	0.45 \pm 20%	2.4(2.0)	26.4	21.2	17.7
CDEP105NP-0R8MC-50	0R8MS	0.8 \pm 20%	4.1(3.4)	20.8	16.7	13.0
CDEP105NP-1R3MC-50	1R3MS	1.3 \pm 20%	5.3(4.4)	16.8	13.4	11.2
CDEP105NP-1R8MC-50	1R8MS	1.8 \pm 20%	7.5(6.2)	13.8	11.0	9.0
CDEP105NP-2R5MC-50	2R5MS	2.5 \pm 20%	10.5(8.7)	11.8	9.6	7.8
CDEP105NP-3R2MC-50	3R2MS	3.2 \pm 20%	12.4(10.3)	10.5	8.4	7.4
CDEP105NP-4R0MC-50	4R0MS	4.0 \pm 20%	18.0(15.0)	9.3	7.4	6.2
CDEP105NP-5R0MC-50	5R0MS	5.0 \pm 20%	23.8(19.8)	8.4	6.7	4.9


Electrical Characteristics3 – High Power Type

PART NO.	STAMP	INDUCTANCE (μ H) ※1	D.C.R. (m Ω) [MAX.] (at 20°C)	SATURATION CURRENT (A) ※2		TEMPERATURE RISE CURRENT (A) ※3 Δ T=40°C
				(at 20°C)	(at100°C)	
CDEP105NP-0R1NC-32	0R1NH	0.15 \pm 30%	1.7(1.4)	55.0	46.0	19.0
CDEP105NP-0R3NC-32	0R3NH	0.3 \pm 30%	2.4(2.0)	40.0	33.0	17.7
CDEP105NP-0R5MC-32	0R5MH	0.5 \pm 20%	4.1(3.4)	30.4	25.0	13.0
CDEP105NP-0R8MC-32	0R8MH	0.8 \pm 20%	5.3(4.4)	25.2	20.7	11.2
CDEP105NP-1R2MC-32	1R2MH	1.2 \pm 20%	7.5(6.2)	21.0	17.4	9.0
CDEP105NP-1R5MC-32	1R5MH	1.5 \pm 20%	10.5(8.7)	18.0	15.0	7.8
CDEP105NP-2R0MC-32	2R0MH	2.0 \pm 20%	12.4(10.3)	15.8	13.1	7.4
CDEP105NP-2R5MC-32	2R5MH	2.5 \pm 20%	18.0(15.0)	14.0	11.7	6.2
CDEP105NP-3R0MC-32	3R0MH	3.0 \pm 20%	23.8(19.8)	12.6	10.5	4.9

※1. Measuring condition: at 100kHz.


※2. Saturation current: The value of D.C. current when the inductance decreases to 65% (while the tolerance is \pm 30%) or 75% (while the tolerance is \pm 20%) of it's nominal.

※3. Temperature rise current: The value of D.C. current when the temperature rise is Δ t=40°C (Ta=20°C).




Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT















SMD Power Inductor CDEP105




Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT






SMD Power Inductor CDEP105




Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT




Solder Reflow Condition

Heat Endurance



Temperature Chart



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong

Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Saitama(Japan)

Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Chicago

Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai

Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Seoul

Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Obernzell

Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen

Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore

Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

Neumarkt

Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei

Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose

Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Sumida:

[CDEP105NP-0R2NC-50](#) [CDEP105NP-0R4MC-50](#) [CDEP105NP-0R8MC-88](#) [CDEP105NP-1R2MC-88](#) [CDEP105NP-1R3MC-50](#) [CDEP105NP-1R4MC-88](#) [CDEP105NP-1R8MC-50](#) [CDEP105NP-2R2MC-88](#) [CDEP105NP-3R2MC-88](#) [CDEP105NP-4R3MC-88](#) [CDEP105NP-5R7MC-88](#) [CDEP105NP-7R2MC-88](#) [CDEP105NP-8R8MC-88](#) [CDEP105NP-4R0MC-50](#) [CDEP105NP-0R5MC-32](#) [CDEP105NP-1R2MC-32](#) [CDEP105NP-2R0MC-32](#) [CDEP105NP-2R5MC-32](#) [CDEP105NP-0R8MC-32](#) [CDEP105-0R1NC-32](#) [CDEP105NP-0R1NC-32](#) [CDEP105NP-2R5MC-50](#) [CDEP105NP-0R3NC-32](#) [CDEP105NP-5R0MC-50](#) [CDEP105NP-2R5MB-50](#) [CDEP105NP-3R2MC-50](#) [CDEP105NP-0R3NC-88](#) [CDEP105NP-0R8MC-50](#) [CDEP105NP-1R5MC-32](#) [CDEP105NP-3R0MC-32](#)