

Electrical Specifications ⁽¹⁾

Operating Temperature Range: ⁽²⁾ -40 to +85 °C

Parameter ⁽³⁾	Minimum	Typical ⁽⁵⁾	Maximum	Unit
Center Frequency	-	140	-	MHz
Insertion Loss @ Center Frequency	-	13.6	15.5	dB
Amplitude Variation 137.25 – 142.75 MHz	-	0.4	1.4	dB p-p
136.50 – 143.50 MHz	-	0.5	1.7	dB p-p
Phase Linearity 137.25 – 142.75 MHz	-	1.8	6.0	° p-p
136.50 – 143.50 MHz	-	2.8	7.6	° p-p
Average Group Delay 137.25 – 142.75 MHz	1.02	1.07	1.12	µs
Input/Output Return Loss 136.50 – 143.50 MHz	10	20	-	dB
Relative Attenuation ⁽⁴⁾ 10 – 132MHz	40	45	-	dB
132 – 133 MHz	35	46	-	dB
147 – 150 MHz	35	43	-	dB
150 – 200 MHz	40	45	-	dB
Triple Transit Suppression	40	60	-	dB
Source Impedance (balanced or single-ended) ⁽⁶⁾	-	50	-	Ω
Load Impedance (balanced or single-ended) ⁽⁶⁾	-	50	-	Ω

Notes:

1. All specifications are based on the TriQuint matching schematics shown on page 5
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. Relative to insertion loss at center frequency
5. Typical values are based on average measurements at room temperature
6. This is the optimum impedance in order to achieve the performance shown

Electrical Specifications ⁽¹⁾

Operating Temperature Range: ⁽²⁾ -20 to +85 °C


Parameter ⁽³⁾	Minimum	Typical ⁽⁵⁾	Maximum	Unit
Center Frequency	-	140	-	MHz
Insertion Loss @ Center Frequency	-	13.6	15.5	dB
Amplitude Variation				
137.25 – 142.75 MHz	-	0.4	1.4	dB p-p
136.50 – 143.50 MHz	-	0.5	1.7	dB p-p
Phase Linearity				
137.25 – 142.75 MHz	-	1.8	6	° p-p
136.50 – 143.50 MHz	-	2.8	7	° p-p
Average Group Delay				
137.25 – 142.75 MHz	1.02	1.07	1.12	µs
Input/Output Return Loss				
136.50 – 143.50 MHz	10	20	-	dB
Relative Attenuation ⁽⁴⁾				
10 – 132MHz	40	45	-	dB
132 – 133 MHz	35	46	-	dB
147 – 150 MHz	35	43	-	dB
150 – 200 MHz	40	45	-	dB
Triple Transit Suppression	40	60	-	dB
Source Impedance (balanced or single-ended) ⁽⁶⁾	-	50	-	Ω
Load Impedance (balanced or single-ended) ⁽⁶⁾	-	50	-	Ω

Notes:


1. All specifications are based on the TriQuint matching schematics shown on page 5
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. Relative to insertion loss at center frequency
5. Typical values are based on average measurements at room temperature
6. This is the optimum impedance in order to achieve the performance shown

Typical Performance (at room temperature)


Frequency Response




Passband Response




Wideband Response




Phase / Group Delay



Input Smith Chart




Output Smith Chart




Matching Schematics

Actual matching values may vary due to PCB layout and parasitics




Marking





The date code consists of: day of the current year (Julian, 3 digits), last digit of the year (1 digit) and hour (2 digits)

PCB Footprint



This footprint represents a recommendation only
Dimensions shown are nominal in millimeters

Tape and Reel




Dimensions shown are nominal in millimeters
Packaging quantity: 4000 units/reel

Maximum Ratings


Parameter	Symbol	Minimum	Maximum	Unit
Operating Temperature Range	T	-40	+85	°C
Storage Temperature Range	T _{stg}	-55	+125	°C
Pyroelectric Voltage	V _{Pyro}	-	50	mV p-p
Input Power	P _{in}	-	+10	dBm

Important Notes

Warnings

- Electrostatic Sensitive Device (ESD) 
- Avoid ultrasonic exposure

RoHS Compliance

- This product complies with EU directive 2002/95/EC (RoHS) 

Solderability

- Compatible with JEDEC J-STD-020C **Pb-free** process, **260°C** peak reflow temperature ([see soldering profile](#))

Links to Additional Technical Information

[PCB Layout Tips](#)

[Qualification Flowchart](#)

[Soldering Profile](#)

[S-Parameters](#)

[RoHS Information](#)

[Other Technical Information](#)

TriQuint's liability is limited only to the Surface Acoustic Wave (SAW) component(s) described in this data sheet. TriQuint does not accept any liability for applications, processes, circuits or assemblies, which are implemented using any TriQuint component described in this data sheet.

Contact Information

TriQuint 
SEMICONDUCTOR
PO Box 609501
Orlando, FL 32860-9501
USA

Phone: +1 (407) 886-8860
Fax: +1 (407) 886-7061
Email: info-product@tqs.com
Web: www.triquint.com

Or contact one of our worldwide
Network of [sales offices](#),
[Representatives or distributors](#)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Qorvo:](#)

[856694](#)