

Termination Interface: Style Through Hole - Compliant Pin

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.75A           |
| Data Rate                     | 25.0 Gbps       |
| Impedance                     | 100Ω            |
| Shield Type                   | N/A             |
| Shielded                      | No              |
| Voltage - Maximum             | 30V AC (RMS)/DC |

**Material Info**

**Reference - Drawing Numbers**

|                           |                                     |
|---------------------------|-------------------------------------|
| Application Specification | AS-76060-990-001, AS-76060-9999-001 |
| Electrical Model Document | EE-76410-002-002                    |
| Packaging Specification   | PK-70873-762-001                    |
| Product Specification     | PS-76060-999-001                    |
| S-Parameter Model         | SP-76410-002-002                    |
| Sales Drawing             | SD-76410-002-001                    |
| Symbol/Footprint Data     | SYM-76410-3607-001                  |

This document was generated on 12/21/2021

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[76410-3607](#)