

Maximum Ratings (@ $T_A = +25$ °C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	Vсво	-60	V
Collector-Emitter Voltage	V _{CEO}	-50	V
Emitter-Base Voltage	VEBO	-6	V
Collector Current - Continuous (Note 5)	Ic	-150	mA

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 5) T _A = +25°C	P _D	150	mW
Thermal Resistance, Junction to Ambient (Note 5)	R _{θJA}	833	°C/W
Operating and Storage Temperature Range	T _J , T _{STG}	-55 to +150	°C

ESD Ratings (Note 6)


Characteristic	Symbol	Value	Unit	JEDEC Class
Electrostatic Discharge - Human Body Model	ESD HBM	4,000	V	3A
Electrostatic Discharge - Machine Model	ESD MM	400	V	С

Notes:

For a device mounted with the collector lead on minimum recommended pad layout 1oz copper that is on a single-sided 1.6mm FR-4 PCB; device is measured under still air conditions whilst operating in a steady-state.
Refer to JEDEC specification JESD22-A114 and JESD22-A115.



Thermal Characteristics and Derating Information






Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Min	Тур	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 7)					•		
Collector-Base Breakdown Voltage		V(BR)CBO	-60	_	_	V	$I_C = -50\mu A, I_E = 0$
Collector-Emitter Breakdown Voltage		V(BR)CEO	-50	_	_	V	$I_{C} = -1 \text{mA}, I_{B} = 0$
Emitter-Base Breakdown Voltage		V(BR)EBO	-6	_	_	V	$I_E = -50\mu A, I_C = 0$
Collector Cutoff Current		Ісво	_	_	-100	nA	Vcb = -60V
Emitter Cutoff Current		IEBO	_	_	-100	nA	V _{EB} = -6V
ON CHARACTERISTICS (Note 7)							
DC Current Gain	2DA1774Q 2DA1774R	h _{FE}	120 180	_	270 390		Vcf = -6V, lc = -1mA
	2DA1774S	142	270		560		162 11,16
Collector-Emitter Saturation Voltage		V _{CE(sat)}	_	_	-0.5	V	$I_C = -50 \text{mA}, I_B = -5 \text{mA}$
SMALL SIGNAL CHARACTERISTICS							
Output Capacitance		C _{obo}	_	4.0	5.0	pF	$V_{CB} = -12V$, $f = 1MHz$, $I_E = 0$
Current Gain-Bandwidth Product		f⊤		140		MHz	V _{CE} = -12V, I _C = -2mA, f = 30MHz

Notes:

Typical Electrical Characteristics (@TA = +25°C, unless otherwise specified.)



vs. Collector Current




Fig. 3 Typical Gain-Bandwidth Product vs. Collector Current


^{7.} Measured under pulsed conditions. Pulse width ≤ 300 µs. Duty cycle ≤ 2%.



Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT523




	SOT523					
Dim	Min	Max	Тур			
A1	0.00	0.10	0.05			
A2	0.60	0.80	0.75			
A3	0.45	0.65	0.50			
b	0.15	0.30	0.22			
С	0.10	0.20	0.12			
D	1.50	1.70	1.60			
Е	1.45	1.75	1.60			
E1	0.75	0.85	0.80			
е	0.50 BSC					
e1	0.90	1.10	1.00			
١	0.20	0.40	0.33			
а	0°		8°			
All Dimensions in mm						

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT523



Dimensions	Value (in mm)
С	1.29
Х	0.40
X1	0.70
Y	0.51
V1	1.80

July 2021



IMPORTANT NOTICE

- DIODES INCORPORATED AND ITS SUBSIDIARIES ("DIODES") MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).
- The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes products. Diodes products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of the Diodes products for their intended applications, (c) ensuring their applications, which incorporate Diodes products, comply the applicable legal and regulatory requirements as well as safety and functionalsafety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.
- Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.
- Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademarks applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.
- subject Diodes products are provided to Diodes' Standard Terms and Conditions of Sale (https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.
- Diodes products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.
- While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.
- Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

Copyright © 2021 Diodes Incorporated

www.diodes.com