

Electrical Specifications (-40°C ≤ T_A ≤ +85°C unless otherwise specified)

INPUT CHARACTERISTICS	Limits	Units
Minimum Input Current (see figure 1)	5.0	mA
Input Current Range (see figure 1)	3.0 to 25	mA
Maximum Continuous Input Current @ $T_A=+25^{\circ}\text{C}$	40	mA
LED Forward Voltage Drop @ 5mA, $T_A=+25^{\circ}\text{C}$ (see figure 3)	1.4	V
Maximum Reverse Voltage	6.0	V
Maximum Reverse Current @ $-6V_{DC}$, $T_A=+25^{\circ}\text{C}$	10	μA


OUTPUT CHARACTERISTICS	Limits	Units
Minimum Forward Voltage	8.0	V _{DC}
Maximum Reverse Current	10	μA _{DC}

COUPLED CHARACTERISTICS		Limits	Units
Minimum Output Voltage @ $I_{LED} = 5mA$, $R_L = 10M\Omega$ @ $T_A = 0^\circ C$ to $+70^\circ C$ (see figures 1 and 2)		3	V
Maximum Output Voltage @ $I_{LED} = 5mA$, $R_L = 10M\Omega$ @ $T_A = 0^\circ C$ to $+70^\circ C$ (see figures 1 and 2)		8	V
Maximum Voltage Differential Between Outputs @ $I_{LED} = 5mA$, $R_L = 10M\Omega$		1.0	V
Typical Output Short-Circuit Current @ $I_{LED} = 5mA$, @ $T_A = +25^\circ C$ (see figures 1 and 2)		1.0	μA
Maximum Turn-On Time @ $I_{LED} = 5mA$, $C_{LOAD} = 200pF$ (see figure 4)		5	ms
Max. Turn-Off Time @ $I_{LED} = 5mA$, $C_{LOAD} = 200pF$ (see figure 4)		0.25	ms
Off-State Clamping Resistance:			
	minimum	100	Ω
	maximum	3300	Ω

GENERAL CHARACTERISTICS		Limits	Units
Minimum Dielectric Strength, Input-Output		3750	V _{RMS}
Minimum Dielectric Strength, Output-to-Output		1200	V _{DC}
Minimum Insulation Resistance, Input-to-Output @T _A =+25°C, 50%RH, 100V _{DC}		10 ¹²	Ω
Maximum Capacitance, Input-Output		5.0	pF
Maximum Pin Soldering Temperature (10 seconds maximum)		+260	°C
Ambient Temperature Range:		-40 to +85	°C
Operating Storage		-40 to +125	°C

Connection Diagram

International Rectifier does not recommend the use of this product in aerospace, avionics, military or life support applications. Users of this International Rectifier product in such applications assume all risks of such use and indemnify International Rectifier against all damages resulting from such use.






Figure 1. Typical Output Characteristics




Figure 2. Typical Variation of Output




Figure 3. Input Characteristics (Current Controlled)




Figure 4. Typical Response Time

01-2004 04

Note: For the most current drawing please refer to IR website at: <http://www.irf.com/package/>

Qualification information[†]

Qualification level	Indusrid (per JEDEC JESD47I ^{††} guidelines)	
Moisture Sensitivity Level	PVI5013RPbF	N/A
	PVI5013RSPbF	MSL4
	PVI5013RS-TPbF	(per JEDEC J-STD-020E & JEDEC J-STD-033C ^{††})
RoHS compliant	Yes	

† Qualification standards can be found at International Rectifier's web site
<http://www.irf.com/product-info/reliability>

†† Applicable version of JEDEC standard at the time of product release.

Revision History

Date	Comment
4/24/2015	- Added Qualification Information table on page 5. - Updated data sheet based on corporate template.

International
 Rectifier

IR WORLD HEADQUARTERS: 101 N. Sepulveda Blvd., El Segundo, California 90245, USA
 To contact International Rectifier, please visit <http://www.irf.com/whoto-call/>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Infineon:](#)

[PVI5013RPBF](#) [PVI5013RS-TPBF](#) [PVI5013RSPBF](#)